

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other
2. NAME OF OPERATOR
Consolidated Oil & Gas, Inc.
3. ADDRESS OF OPERATOR
P.O. Box 2038, Farmington, N.M. 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1450' FSL & 1105' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
SF 078464
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Cain
9. WELL NO.
1E
10. FIELD OR WILDCAT NAME
Gallup/ Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 25, T31N, R13W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
30-045-24321
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5980'KB, 5968'GL

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐ ☐
- FRACTURE TREAT ☐ ☐
- SHOOT OR ACIDIZE ☐ ☐
- REPAIR WELL ☐ ☐
- PULL OR ALTER CASING ☐ ☐
- MULTIPLE COMPLETE ☐ ☐
- CHANGE ZONES ☐ ☐
- ABANDON* ☐ ☐
- (other) X"Set BP & TA DK Zone"

RECEIVED

SEP 28 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We hereby request approval to pull Dakota and Gallup 1-1/2" tubing and production packer. A drillable bridge plug will be set at 6500' & the Dakota zone temporarily abandoned. Run 2-3/8" tubing and rods, return Gallup to production. The Dakota is not capable of production due to the excess water production & Gallup requires pumping because of oil production.

Provide for the installation of a bridge plug or a cement plug no more than 50 feet above the Dakota perforations, and the well bore filled with conditioned, non-corrosive fluid, and shut in at the surface. If a bridge plug is used, it must be capped with cement. The cement cap must be the greater of 35 feet or five sacks of cement if placed by dump bailer or, 25 sacks if spotted by tubing. If a cement plug is used it must be the greater of 100 feet or 25 sacks of cement.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drlg. & Prod. Sup't. DATE 9-28-83

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AS AMENDED

FARMINGTON COPY
NM000 D.

SEP 30 1983
M. MILLENBACH
MANAGER

