

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other
2. NAME OF OPERATOR  
Consolidated Oil & Gas, Inc.
3. ADDRESS OF OPERATOR  
P. O. Box 2038 Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1450' FSL & 1105' FEL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- |                      |                                     |
|----------------------|-------------------------------------|
| TEST WATER SHUT-OFF  | <input type="checkbox"/>            |
| FRACTURE TREAT       | <input checked="" type="checkbox"/> |
| SHOOT OR ACIDIZE     | <input type="checkbox"/>            |
| REPAIR WELL          | <input type="checkbox"/>            |
| PULL OR ALTER CASING | <input type="checkbox"/>            |
| MULTIPLE COMPLETE    | <input type="checkbox"/>            |
| CHANGE ZONES         | <input type="checkbox"/>            |
| ABANDON*             | <input type="checkbox"/>            |
| (other)              |                                     |

--	--	--	--	--	--	--

RECEIVED (NOTE: Report chan  
NOV 10 1980  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10-25-80 Perf. at 6105,07,09,11,13,15,17,19,21,23,25,27,29,31,33,35,37,39.

10-26-80 Acidize with 500 gal. 7½% NE HCL.

10-29-80 Frac. with 19,110 gal 30# gel & 6,600 # 10-20 sand.  
Max. pressure 3800. Average pressure 3200. AIR 15 BPM.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED A. A. Anderson TITLE Drilling Supt. DATE 11/5/80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE \_\_\_\_\_

\*See Instructions on Reverse Side

Need  
Name Change  
Q 15

BY BW

