

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator <i>Continental Oil & Gas, Inc.</i>	8. Farm or Lease Name Templeton
3. Address of Operator P.O. Box 2038 Farmington, New Mexico 87401	9. Well No. 1-E
4. Location of Well UNIT LETTER B 890 FEET FROM THE North LINE AND 1820 FEET FROM THE East LINE, SECTION 27 TOWNSHIP 31-N RANGE 13-W NMPM.	10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 5580' G1	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-9-80 Drilled 263' of 12 1/4 hole. Ran 6 jts of 8 5/8" 24# V-55 csg. Cemented w/250 SX Class B + 2% Ba Cl and 1/4# Celloflake a sack. Circulate 4 bbl to surface.
7-27-80 Drilled 6630' of 7 7/8" hole. Schlumberger ran IES, FDC/CNL/GR Caliper.
8-4-80 Ran 10 joints of 5 1/2" N-80 17# CSG and 160 joints of 5 1/2" 15.5# K-55 csg. Cemented 1st stage w/425 sacks 50/50 poz + 2% Gel and 6% Halad 9 and 1/4# Flocele a sack. Cement 2nd stage w/425 sacks 50/50 poz and 2% Gel + 1/4# Flocele a sack. Cemented 3rd stage w/425 sacks 65/35 .6% Halad 9 and 1/4# Flocele a sack, followed w/ 350 sacks 50/50 poz and 2% Gel and .6% Halad 9 + 1/4# Flocele a sack. Circulate 40 Bbls cement to surface. Plug Down @ 4:30 PM

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Frank T. Chavez*

TITLE **Drilling Superintendent**

DATE **8-6-80**

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT **1**

DATE **AUG 7 1980**

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY: