Budget Bureau No. 42-R1424

5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME.
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME SELECTION OF SELECTIO
1 oil gas -	8. FARM OR LEASE NAME A COMPANY OF THE LANGENDORF & COMPAN
vell gas well other	9. WELL NO 9 5 5 4 5 5 5 5
2. NAME OF OPERATOR	1-E page land Carte
CONSOLIDATED OIL AND GAS INC.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin-Dickola
P.O. BOX 2038 FARMINGTON, NEW MEXICO	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA 55 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
below.) 1100' FSL & 1100' FEL AT SURFACE:	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	SAN JUAN NEW MEXICO
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5875' GR
TEST WATER SHUT-OFF	$\mathcal{Z}_{\mathcal{L}}^{-1} = \mathcal{Z}_{\mathcal{L}}^{-1} + \mathcal{Z}_{\mathcal{L}}^{-1} + \mathcal{Z}_{\mathcal{L}}^{-1}$
FRACTURE TREAT	및 취료 및 기계 및 기
SHOOT OR ACIDIZE	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	그는 그는 하는 그렇다면 그 뭐 그런 생각이 되는
CHANGE ZONES	
(other) CASING TEST- CEMENT JOB	
6-1-80: Drill 275' of 12-1/4" hole. Ran 6 Set at 268'. Cemented w/275 sx Cl. B w/2% Ca 6-14-80: Drill 7-7/8" hole 6806'. Logged w, 6-15-80: Ran 173 jts. 5-1/2", K-55, 15.5# 3 475 sx 50-50 poz w/2% gel, 1/4# floseal/sx ar Cemented 2nd Stage w/430 sx 50-50 pox w/2% ge Cemented 3rd Stage w/ 300 sx 65-35 pox w/.6% and 1/4# floseal/sx and .6% Halad 9. Ran Temp. survey. Found top of cement @ 500 Plug Down @ 10:15, 6-15-80.	AC1. Cir. 14 Bbls. / Schlumberger IES, FDC/CNL. ST&C Casing. Cemented 1st Stage wind .6% Halad 9 at 68351. el, 1/4# floseal/sx and .6% Halad gel and 400 sx 50-50 pox w/2% gel
Subsurface Safety Valve: Manu. and Type	Set @ 5 COM: Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED DRILLING SI	JPT. DATE 6-25-80
(This space for Federal or State off	ice use)
APPROVED BY TITLE	DATE DATE
CONDITIONS OF APPROVAL, IF ANY:	1995 Hand Bulleton (1995)
	English Constitution of the Constitution of th
*See Instructions on Reverse	side AUSEPTED TEST CALCULAN

JUL 7 1980

BY BARMINGTON