UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM 021125
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
Total Total State of the State of Proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	Jackson 9. WELL NO.
2. NAME OF OPERATOR Consolidated Oil & Gas, Inc.	2-E 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
1860 Lincoln St. Denver, Colorado 80295	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) AT SURFACE: 815' FSL & 1550' FEL	Sec. 18 T-31-N, R-12-W
AT TOP PROD. INTERVAL: 815' FSL & 1550' FEL	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San Juan New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5980' GL
	and the second second
FRACTURE TREAT	CON COLOR OF TON, N. M.
SHOOT OR ACIDIZE	EIVED / [
REPAIR WELL	(NOTE: Report results of multiple completion
PULL OR ALTER CASING AUG 2	3 198 Uchange or Form 9-330.)
MULTIPLE COMPLETE	20%
ABANDON* U. S. GEOLO	GICAL SURVEY
(other) Casing & Cement	GICAL SURVEY TON, N. M.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinen	irectionally drilled give subsurface locations and
8-4-80 Drilled 12 1/4" surface hole to 262"	Ran 6 Joints, 2461 8 5/8"
24# St & & J-55 casing set at 260!. Cement with 200 sacks Class	
"B" with 2% calcium Chloride. Circu	llate 84 sacks.
8-17-80 Drilled 7 7/8" hole to 7085'. Dress	ser Atlas Ran IES w/SP & GR
and FDC/CNL/GR.	
8-18-80 Ran 162 Joints 4 1/2" 10.5# & 11.6#,	K-55 & N-80 casing, 7073
set at 7085. Cemented 1st stage wi	th 400 sacks 50450 nov.
2% Gel & 1/4# floceal. Cemented 2nd	stage with 480 eacks
65/35 poz. containing 6% Gel & 1/4#	
with 520 sacks 65/35 poz. 6% Gel & 1	110cear. Cemented 3rd stage
barrels cement to sunface. DV tools	A 50221 COORT
Darrers Cement to Symtace. DV Loors	5 @ 3033
Subsurface Safety Valvey Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	200 년 1월 1일
SIGNED A face Lichardson TITLE DRILLING Su	47 DATE 8-20-80
(This space for Federal or State offi	ce use)
APPROVED BY TITLE	DATE
CONDINCTED FOR RECORD	도로 취임된 기능한 실험하 라요

AUG 27 1980

*See Instructions on Reverse Side

ARMINGTON DISTRICT