

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Bruce Anderson

3. ADDRESS OF OPERATOR

Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1780' FSL - 1100' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) ☐

SUBSEQUENT REPORT OF:

☒☐☐☐☐☐☐☐☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-19-80 1730' T.D. - Ran Welex - IES log - Prep to run csg.

8-20-80 Ran 62 jts - 2-7/8" O.D., 6.4# JCW - 10R NEVE. Coad A tbgs. set at 1718. Cementers, Inc. cemented w/50 sx 2% lodense and 100 sx class "B" neat. Total slurry 228 cu. ft. Good circulation while cementing. Clear water to surface but no cement - reciprocated tbgs. while cementing. P.O.B. 8-19-80. - Good job. Release Morrow Drlg.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Thomas A. Dugan TITLE Engineer DATE 8-21-80

(This space for Federal or State office use)

APPROVED FOR RECORD \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY

AUG 27 1980

FARMINGTON DISTRICT

BY BW

\*See Instructions on Reverse Side

NMOCC

