UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Form 9–331 Dec. 1973	Foring Approved. Budget Bureau No. 42–R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-021126
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
1. oil gas X other	8. FARM OR LEASE NAME Newman
Well Other	9. WELL NO.
2. NAME OF OPERATOR	1-E
Consolidated Oil and Gas	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 1860 Lincoln St. Suite 1300 Denver. Colo.802	Basin Dakota
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	9 5 1. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	Sec. 20 T31N R12W
AT SURFACE: 830' FNL \$ 1610' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San Juan NM
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO.
, ,	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5991 ' GL
TEST WATER SHUT-OFF []	
FRACTURE TREAT SHOOT OR ACIDIZE FRACTURE TREAT FRACTURE TRE	
REPAIR WELL	CEIVED
	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE	change on Form 9-330.)
CHANGE ZONES	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent	rectionally drilled, give subserface locations and
9-2-80 Drilled 255' 12½" surface. Ran 6 jt 20# casing landed at 253'. Cemented	with 200 sacks
class "B" contain 2% CaCl. Circ. 5	sacks cement.
9-16-80 Drilled 7 7/8" hole to 71801. Schlim	mberger ran IES/CD EDC CNI

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form $9-331C$ for such proposals.)						-
1.	oil well		gas well	X	other	
2	NAM	F OF	OPERA:	TOR		

9-16-80 Drilled 7 7/8" hole to 7180'. Schlumberger ran IES/GR, FDC, CNL.

9-17-80 Ran 164 jts 4½" 10.5# & 11.6#, J-55 & N-80 casing set at 7171'. with DV tools at 2539' & 5145'. Cemented first stage with 230 sx 50-50 poz 2% Gel. Good circ. Cemented 2nd 300 sx 65-35 poz, 6% gel, & ½# flocele/sx. Good circ. Cemented 3rd stage with 550 sx 65-35 poz, 6% gel. Good circ. Circ 30 BBL cement to surface.

Subsurface Safety Valve: Manu. and Type	lanu. and Type		FI	
18. I hereby certify that the foregoing is true	and correct	Set @		
		9-19-80		
	This space for Federal or State office use)			
•	The special service of the condition of			

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECUMD

OCT 0 4 1980

*See Instructions on Reverse Side