

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Supron Energy Corp. c/o Gordon L. Llewellyn
3. ADDRESS OF OPERATOR Suite 140, Campbell Centre
8350 N. Central Expwy. Dallas, Texas 75206
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1090' FNL & 1080' FEL (NW NW)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☒
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:


- ☐
☐
☐
☐
☐
☐
☐
☐
☐

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Total depth 7 7/8" hole drilled to 5036'.
2. Ran 131 joints (5017'), 4 1/2", 10.5#, K-55, R-3, ST&C casing.
3. Set and cemented at 5017'.
4. Cemented w/1195 sacks 50/50 pozmix, 6% gel, 1/4# cello-flake. Tailed in w/200 sacks Class B cement.
5. Test water shut-off to 2000# w/10", 900 series Shaffer Blow out Preventor.



Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Harman L. Wallis TITLE Superintendent DATE OCT 18 1980

REGISTERED FOR RECORD (This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL IF ANY: OCT 18 1980

BY BW FARMINGTON DISTRICT