5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	NM-33053
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAE SORVET	N/A
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
SUNDRY NUTICES AND INC. Of the state of the	N/A
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas [Y]	Trail Canyon
well well other	9. WELL NO. 3
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME
Oxoco Production Corp.	Blanco MV - Basin DK
3. ADDRESS OF OPERATOR	11. SEC., T., R., M., OR BLK. AND SURVEY OR
Box 255, Farmington, N.M. 87401	AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	S7-T32N-R8W, NMPM
below.) AT SURFACE: 2050 ft. fS1, 430 ft. fE1	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	30-045-24622
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	6695' Gr.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TECT WATER CHITOFF	rape, magalatur t. * 3
FRACTURE TREAT	
SHOOT OR ACIDIZE	(NDTE: Report results of multiple completion or zone
REPAIR WELL BUIL OR ALTER CASING	change on Form 9-330.)
MILITIPLE COMPLETE	
CHANCE TONES ULS. GEOLOGICAL SOIL	2 4
ABANDON*	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 5/26/82Ran 97 jts. 7 5/8", 26.	ent to this work.)* 4.15 K_55 ST&C. 8-rnd.
insert float). Landed casing at 3896' izers at 3853', 3774', 3692', 3617' a chemical wash followed by 150 sk. 65, 6½ 1b./sk. gilsonite followed by 175 2% CaCl2 and ½ 1b./sk. cellophane fla 6 BPM at 300 psi max. press. Displace water at 8 BPM and 1000 psi max. press.	y, w/float at 3853' and central and 3496'. Pumped 20 bbls. /35 Pozmix with 12% gel and sk. Class B cement with akes. Pump rate during mixing add with 180.5 bbls. fresh
temp. survey. Top cement at 1900'.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct Agent	DATE May 26, 1982
(This space for Federal D. State (Price (Page)	
APPROVED BY TITLE TITLE TOTAL	
CONDITIONS OF APPROVAL, IF ANY:	
	138%
1 2015	s com: 1982
*See Instructions on Rever	Side Side
- 266 Histigerian an in	FARMINGTON PROPERTY

NMOCC