

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
SOLAR PETROLEUM, INC.
3. ADDRESS OF OPERATOR 80202
One Denver Pl., #1300, 999 18th St., Denver, CO
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1405' FSL, 1330' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) SPUD & CASING RECORD ☒

SUBSEQUENT REPORT OF

☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

JUN 30 1981

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location and measured and true vertical depths for all markers and zones pertinent to this work.)*

SPUD DATE: 2/11/81 @ 2:00 p.m.
DATE TO REACHED: 3/5/81
DATE COMPLETED: 5/9/81
TD: 1135'

SET 8-5/8" csg w/ 100 sx Class 'B', 1/4#/sx flake, 3% cc (12-1/2" hole) @ 90' w/
3 bbls to sfc.

SET 4-1/2" csg w/ 150 sx 50/50 POZ, 10% salt, 2% cc, 150 sx Class 'B' Neat (6-1/2" hole) @ 1129' w/ 13 bbls to sfc.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Clean J. Stone TITLE Sr Pet. Engineer DATE June 26, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NMOCC

JUL 9 1981

*See Instructions on Reverse Side

FARMINGTON DISTRICT
BY h

