## Form Approved. Budget Bureau No. 42-R1424

5. LEASE

SF 078119

## UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9, 222.	7. UNIT AGREEMENT NAME
reservoir, ose form 5–351±C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas □ other P&A	Suter
2. NAME OF OPERATOR	9. WELL NO.
Mesa Petroleum Co.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 1660 Lincoln St. #2800, Denver CO 80264	Blanco Pictured Cliffs
4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.) AT SURFACE: 1820' FNL 8 1700' FML	Sec. 13-T32N-R11W
at surface: 1820' FNL & 1790' FWL at top prod. interval:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San Juan New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	
	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6265' GL
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	The second
REPAIR WELL	T STORE STOR
PULL OR ALTER CASING	MO(E: Report results of multiple completion or zone change on Form 9-330.)
MULTIPLE COMPLETE  CHANGE ZONES	JUL 90
ABANDON* □	JUL 28 1982
(other) Subsequent Notice of Abandonment	William
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent	rectionally drilled, give subsurface locations and to this work.)*
Subject well was plugged and abandoned on 4/22 from 3133' to 2939'; 80 sacks across the Pictuwas placed from 2570' to 2470'; 50 sacks acroswas placed from 2200' to 2100'; 50 sacks acroswas placed from 1200' to 1060'; 50 sacks acroswas placed from 275' to 175'; 50 sacks, ½ in 10 sack plug at surface with dry hole marker. filled with mud laden fluid.	red Cliffs. Second cement plug s the Fruitland. Third cement plug s the Kirtland. Fourth cement plug s the Ojo Alamo. Fifth cement plug and bout of surface casing. Set
in the second	
A A	NC 01 mag
	con DIV.
Subsurface Safety Valve: Manu. and Type	CON. DIV. Set @Ft.
18. I hereby certify that the foregoing is true and correct	DIS1. 3
SIGNED Kandy Mordsucn TITLE Reg. Coordina	
(This space for Federal or State office	
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	DDR()VLV
	AFFIC
*See Instructions on Reverse Si	APPROVED  GEODINA MILLENBACH

M. MILLENBACH AREA MANAGER