

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name Schneider Gas Com "B"
3. Address of Operator 501 Airport Drive, Farmington, NM 87401	9. Well No. 15
4. Location of Well UNIT LETTER M 950 FEET FROM THE South LINE AND 900 FEET FROM THE West LINE, SECTION 28 TOWNSHIP 32N RANGE 10W NMPM.	10. Field and Pool, or Wildcat Undesignated Fruitland
15. Elevation (Show whether DF, RT, GR, etc.) 6063' GL	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Spud and Set Casing ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12 1/4" hole on 4-15-81, and drilled to 307'. Set 9 5/8" 32.3# surface casing at 299 on 4-16-81, and cemented with 350 sx of class "B" neat cement containing 2% CaCl₂. Good cement was circulated to the surface. Drilled a 8 3/4" hole to a TD of 2826'. Set a 7" production casing at 2826' on 4-20-81, and cemented with 445 sx of class "B" neat cement containing 50/50 POZ, 6% gel, 2# medium tuf plug per sack, and .8% fluid loss additive. This was tailed in with 100 sx of class "B" neat cement. The rig was released on 4-21-81.



CONFIDENTIAL

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed By
E. E. SVOBODA

SIGNED _____ TITLE Dist. Admin. Supvr. DATE 5-1-81

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT # 3

APPROVED BY _____ TITLE _____ DATE MAY 4 - 1981

CONDITIONS OF APPROVAL, IF ANY: