

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Northwest Pipeline Corporation
3. ADDRESS OF OPERATOR  
P.O. Box 90, Farmington, N.M. 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1080 FNL & 1540 FEL NW/NE  
AT TOP PROD. INTERVAL: 1080 FNL & 1540 FEL  
AT TOTAL DEPTH: 1080 FNL & 1540 FEL
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) Spud, Intermediate csg & Production csg.

SUBSQUE

RECEIVED

NOV 15 1982

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6763' KB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10-25-82 MOL & RU. Spudded surface hole at 1900 hrs. Ran 5 jts 9-5/8" 32.3#, H-40, ST&C csg & set at 235' KB. Woodco cmt'ed w/ 220 sx (260 cu.ft) C1 "B" w/ 1/4# Flocele/sx & 3% CaCl<sub>2</sub>. Displaced w/ 16 bbls of wtr

10-26-82 Plug down at 0315 hrs. Circ out 5 bbls of cmt. WOC. Press test csg to 600# - OK. Drlg ahead w/ wtr.

10-27-82 to 10-29-82 Drlg ahead w/ wtr.

10-30-82 Gearhart ran IES & CNL/FDC/GR logs.

10-31-82 to 11-1-82 Ran 104 jts of 7" 23#, K-55, & 20#, K-55, csg & set at 4030' KB. Dowell cmt'ed w/ 135 sx (296 cu.ft) C1 "B" 65/35 poz w/ 12% gel. Tailed w/ 100 sx (118 cu.ft) of C1 "B" w/ 2% CaCl<sub>2</sub>. Displaced plug w/ 158 bbls of wtr & bumped plug at 1415 hrs 10-31-82. WOC 12 hrs. Ran temp survey - top of cmt at 1700'. (Ojo Alamo at 2386'). Press Test csg to 1200# OK

Subsurface Safety Valve: Manu. and Type

CONTINUED ON REVERSE SIDE.

18. I hereby certify that the foregoing is true and correct

SIGNED Donna J. Brace TITLE Production Clerk DATE 11-10-82  
Donna J. Brace

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY.

TITLE

ACCEPTED FOR RECORD

B  
djb/ 1

NMOCC

NOV 16 1982

\*See Instructions on Reverse Side

FARMINGTON DISTRICT

BY

Smm

10-31-82 to 11-1-82 Blew down w/ nitrogen. Drlg w/ gas

11-2-82 TD'ed hole of 6250'. Gearhart ran IES & SNP/FDC/GR logs. Ran 56 jts of 4-1/2", 10.5#, K-55, ST&C csg & set from 3863' to 6248' KB. Dowell cmt'ed w/ 240 sx (430 cu.ft) of C1 "B" w/ 4% gel & 12-1/2# gils/sx. Displaced plug w/ 54 bbls & down at 2345 hrs 11-2-82. Reversed out 10 bbls of cmt.

11-3-82. Rig released at 0430 hrs .

NOW WAITING ON COMPLETION.

118  
296  
414