

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Attention:

Amoco Production Company

Mike Curry

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

(303) 830-4075

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1030' FNL

840' FNL

Sec. 34 T 31N R 10W NW/4NW/4

5. Lease Designation and Serial No.

SF-080917

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Atlantic #1E

9. API Well No.

3004525860

10. Field and Pool, or Exploratory Area

Blanco Pictured Cliffs

11. County or Parish, State

San Juan

New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Workover/Recompletion

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Amoco plans to workover and recomplate the well per the following procedures:

1. POH with PKR and TBG. PKR set at 5317'.
2. RIH with bit and scraper to liner top at 5373'.
3. Cleanout to PSTD of 7440' with Nitrogen if Dakota Perfs are covered by fill.
4. RIH with RBP and set at 5350'. Cap with sand.
5. Run Cement Bond Log over 7" casing.
6. Isolate any leaks in 7" casing and cement squeeze same.
7. RIH with RBP and set at 3000'. Cap with sand.
8. Perforate Pictured Cliffs pay 2936'-2981' and fracture stimulate.
9. RIH with 2 3/8" TBG for the DK, PKR to isolate the producing zones and 2 1/16" TBG for the PC. DK TBG to be landed at 7402' and PC TBG to be landed at 2981'. The PKR will be set at 3081'.
10. Install production equipment and return well to production as a dual DK/PC producer.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Business Analyst

Date

10-14-1994

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

APPROVED

OCT 2 1994

WILLIAM J. MANNING

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.