Form 3160-5 (June 1990))

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

anca Decige	orion and	Camal Mr.
Expires	s: March	31, 1993
Buaget Bi	ureau No.	1004-0135

6.	If Ind	lian.	Allottee	or .	Tribe	Name
	NM	01	3642			
٦.	Lease	/Des	ignation	ano	Sena	u No.

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

NA

(Note: Report results of multiple completion on Well

SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well	NA
Oil Gas Well Other	8. Well Name and No.
2. Name of Operator	- Alban
Koch Exploration Co.	9. API Well No.
3. Address and Telephone No.	
P.C. Box 2256 Wichita, KS 67201	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Basin Fruitland Coal
). 11501 DVI c 10001 DDI	11. County or Parish, State
1170' FNL & 1820' FEL	San Juan New Mexico
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBNICION TYPE OF ACTION	
Notice of Intent A Abandonment	Change of Plans
Recompletion	New Construction
Subsequent Report JAN1 8 1991 Plugging Back	Non-Routine Fracturing
Casing Repair	Water Shut-Off
Final Abandonmen CON. DIV Casing Repair	Conversion to Injection
DIST. 3 XX Other Casing Set	Dispose Water

Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spyd-10/30/90

or representations as to any matter within its jurisdiction

Drld 12 1/4" hole to 222'. Ran 5 jts. 9 5/8' 36# ST&C csg. Set @ 222' with 110 sx Class B cmnt. Circulated.

Drld 8 3/4" hole to 3350'. Ran 75 jts. 23# K-55 LT&C csq.(3342'). Set @ 3350' with 490 sx Lite, tail in with 100 sx Class A cmnt. Good circulation throughout job. Ran temperature survey from 3277 to surface. Top of cement found at 850 from surface.

I hereby certify that the foregoing is true and correct Signed Kunneth Supmour	Administrative C	Coordinator Nov. 6 1990
(This space for Federal or State office use)		ACCEPTED FUNDAMENT
Approved byConditions of approval, if any:	Title	DE Part 1 1990
		FARMINGTON RESOURCE AREA