Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No. SF-079353

FARMINGTON RESOURCE AREA

SUNDRY NOTICES AND REPORTS ON WELLS

6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE San Juan 32-8 Unit 1. Type of Well Oil Gas Well 8. Well Name and No. Other 250 2. Name of Operator 9. API Well No. PHILLIPS PETROLEUM COMPANY 3. Address and Telephone No. 30-045-28307 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal Unit M, 1276' FSL & 868' FWL 11. County or Parish, State Sec. 33, T32N, R8W San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Abandonment Change of Plans Notice of Interit Recompletion **New Construction** Plugging Back Non-Routine Fracturing Subsequent Report Casing Repair Water Shut-Off Conversion to Injection Altering Casing Other As Per NTL-FRA-90-1 Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. _ Time Completed: Time Started: 0610 10-26-90 Date: Casing Size 7" 23# J-55 New Casing Seat Ft. Hole Size 8-3/4" , 2402', 2358' Turbo Centralizers at 2446' Spring Type Centralizers at 3164', 3092' BBls, Spacer 10 Fresh Water. Mud Flush 10 Lead Slurry 500 Sx 65/35 Poz, 12% Gel, 1/4# Flocele/Sk, 11.7 ppg @ 2.3 Ft. 3/Sx yield. Mid Slurry _____ Tail Slurry 150 Sx Class G, 1/4# Flocele/Sk, 15.8 ppg @ 1.15 Ft.3/Sx yield Displaced Plug with 122Bbls Fresh Water. 160 Ben Sacks Volume Cement Circulated PSI, Average Rate 7 BPM, Bumped Plug with 1500 PSI. Average Pressure 370 R. A. Allred 10-31-90 Tide Drilling Supervisor (This space for Federal or State office use)

or representations as to any matter within its jurisdiction.