

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other SWD	5. Lease Designation and Serial No. SF-078998
2. Name of Operator Phillips Petroleum Company	6. If Indian, Allottee or Tribe Name 3: 14
3. Address and Telephone No. 5525 Hwy 64 NBU 3004, Farmington, NM 87401	7. If in California, Agreement Designation UNIT 11
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit M , 735' FDL & 761' FWL Sec. 34 , T32N, R 7W	8. Well Name and No. 301 SWD
	9. API Well No. 30-045-28347
	10. Field and Pool, or Exploratory Area Undesig. Morrison Entrada
	11. County or Parish, State San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input checked="" type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other _____	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion as Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7-11-91

MIRU Four Corners Rig #15. Spud 17-1/2" hole. Drilled to 315'.

7-12-91 thru 7-15-91

Opened hole to 26". and ran 20", 94#, K-55 casing and set @ 441'. RU Western and cemented w/452 sx Class B cement with 1/4# Flocele/sk followed by 250 sx Class B cement w/2% CaCl<sub>2</sub>/sk and 1/4# Flocele/sk. Plugged down @ 0430. Circ. 250 Sx cement to surface. Bumped plug w/1000 psi. Float held. WOC 12 hours. NU BOP and choke manifold. Pressure tested to 1500 psi - okay.

RECEIVED  
AUG 27 1991

ACCEPTED FOR RECORD  
AUG 16 1991

OIL CON. DIV  
DIST. 3

FARMINGTON RESOURCE AREA

14. I hereby certify that the foregoing is true and correct

Signed R. A. Allen

Title Drilling Supervisor

Date 7-22-91

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

NMOOD