

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

070 FARMINGTON, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

SG INTERESTS I LTD

3. Address and Telephone No.

PO Box 338, Ignacio, CO 81137 (303) 563-4000

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1195' FNL, 1150' FEL Sec 27-T31N-R10W

5. Lease Designation and Serial No.

NM 0606

6. If Indian, Allottee or Tribe Name

--

7. If Unit or CA, Agreement Designation

--

8. Well Name and No.

HART CANYON 27-1

9. API Well No.

30-045-29093

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other 5-1/2" csg set

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drld 7-7/8" O.H. to 3136', circ @ TD. Rn FDC/CNL/GR/HRD/Microlog/Caliper Log, LTD 3135'. Circ hole. Rn 100 jts (3120.80') 5-1/2" 17# LS 8 rd LT&C csg; set @ 3134'. Rn 22 centralizers, float collar @ 3099'. Circ @ TD, full returns. Cem as follows: drop btm plug; pmp 10 B/CaCl₂ wtr; 5 BW, 10 B/Zone Lock; 10 BW; 15 B/10 ppg scavenger slurry; 342 sx (773 cu ft) Class "G" plus 2% Sodium Metasilicate plus 1/4#/sk Celloflake plus 5#/sk Kolite, mixed @ 12.2 ppg. Tail in w/100 sx (115 cu ft) Class "G" plus 2% CaCl₂ plus 1/4#/sk Celloflake. Displace w/72 BW. Good circulation thruout job. Circ scavenger slurry (15 bbls) plus 18 B/good cem to surface. Final pmp press 880 psi; bump plug w/1460 psi, float held. PD 1:15 am 3/6/94. ND BOP, set slips, rel rig @ 2:45 am 3/6/94.

Rn CBL/GR/collar locator w/0 pressure. Cem indicated up to inside 8-5/8" surface casing.

14. I hereby certify that the foregoing is true and correct

Signed Marcia M. Cracker

Title Production Tech

Date August 23, 1994

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

FARMINGTON DISTRICT OFFICE

BY SM