

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

5. LINEAR DESIGNATION AND SERIAL NO.

SE-078507

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 32-9 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 32-9 Unit #115

9. API WELL NO.

30-045-29152

10. FIELD AND POOL, OR WILDCAT

Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec 1, T-31-N, R-10-W

12. COUNTY OR PARISH
San Juan

13. STATE
NM

1a. TYPE OF WELL:

OIL WELL ☐

GAS WELL ☒

DRY ☐

OTHER ☐

b. TYPE OF COMPLETION:

NEW WELL ☐

WORK OVER ☐

DEEP-EN ☐

PLUG BACK ☐

DIFF. REMVR. ☐

Other ☐

2. NAME OF OPERATOR

Meridian Oil Inc.

3. ADDRESS AND TELEPHONE NO.

PO Box 4289, Farmington NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

1640' FSL, 975' FWL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

6-23-94

16. DATE T.D. REACHED

6-28-94

17. DATE COMPL. (Ready to prod.)

7-12-94

18. ELEVATIONS (DF, RKB, RT, GS, ETC.)*

6577 GR

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

3700

21. PLUG BACK T.D., MD & TVD

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0-3700

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

3392-3552

25. WAS DIRECTIONAL SURVEY MADE

26. TYPE ELECTRIC AND OTHER LOGS RUN

Ind. GR, SP, CNT, LDT, MLT, CAL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8	24#	220	12 1/4	235 sx (418 cu.ft.)	
4 1/2	10.5#	3700	7 7/8	1426 cu.ft.	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8	3505	

31. PREPARATION RECORD (Injecting fluid and number)

3392-3552

RECEIVED
SEP - 2 1994
OIL CON. DIV.
DIST. 3

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3392-3552	150,800# 20/40 Arizona sd
	21,312 gal x-link gel
	440,000 SCF N2

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
7-12-94		Flowing				SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
8-1-94	3	3/4	→				
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
345	355	→		1971			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

S. Terwilliger

35. LIST OF ATTACHMENTS

None

BHP @ 3500' 376

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

[Signature]

TITLE Regulatory Affairs

DATE

ACCEPTED FOR RECORD
AUG 8 1994

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

DV

Shm

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries);

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH

38. GEOLOGIC MARKERS

Ojo Alamo	1738'	1874'	White, cr-gr ss.	Ojo Alamo	1738'	
Kirtland	1874'	2954'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	1874'	
Fruitland	2954'	3390'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	2954'	
Pictured Cliffs	3390'	3700'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3390'	