

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1090' FSL, 1095' FEL, Sec. 14, T-32-N, R-10-W, NMPM

5. Lease Number
SF-078504

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 32-9 Unit

8. Well Name & Number

San Juan 32-9 U #119

9. API Well No.

30-045-29224

10. Field and Pool

Blanco Pict. Cliffs

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

8-6-97 MIRU. ND WH. NU BOP. TOOH w/2 3/8" tbg. TIH w/gauge ring to 3510'. TOOH. TIH w/CIBP, set @ 3505'. TOOH. TIH to 3504'. Load hole w/1 1/2 Kcl wtr. PT csg & CIBP to 500 psi, OK. Plug #1: pump 12 sx Class "B" neat cmt inside csg @ 3404-3504'. TOH to 3142'. Plug #2: pump 12 sx Class "B" neat cmt inside csg @ 3042-3142'. TOOH to 2850'. Reverse circ hole clean w/23 bbl wtr. TOOH to 2354'. SDON.

8-7-97 TOOH. TIH w/pkr, set @ 128'. PT csg to 3500 psi, OK. TOOH w/pkr. TIH, tag TOC @ 2900'. Perf Farmington sd @ 2420-2430', 2496-2504', 2529-2534', 2780-2785' w/2 SPF. TOOH. TIH w/pkr, set @ 2388'. Spot 50 bbl 1 1/2 KCL wtr in Farmington sd @ 2420-2785'. Blow well & CO. SDON.

8-8-97 Blow well & CO. TOOH. TIH w/pkr, set @ 2380'. Blow well & CO. SD for weekend

8-11-97 Blow well & CO. TOOH w/pkr. TIH w/cmt retainer, set @ 2381'. TOOH. Load hole w/wtr. PT cmt retainer to 1000 psi, OK. Plug #3: pump 62 sx Class "B" neat cmt below cmt retainer outside csg @ 2381-2785'. Pump 5 sx Class "B" neat cmt inside csg above cmt retainer to 2330'. TOOH to 1991'. Plug #4: pump 15 sx Class "B" neat cmt @ 1821-1991'. TOOH to 711'. Circ hole clean. Plug #5: pump 12 sx Class "B" neat cmt @ 561-711'. TOOH. Circ hole clean. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed Deane W. Spencer Title Regulatory Administrator Date 9/3/97

(This space for Federal or State Office use)

APPROVED BY IS/Deane W. Spencer Title

Date SEP 10 1997

CONDITION OF APPROVAL, if any:

NMOCD

8-12-97 TIH, tag TOC @ 491'. Perf 3 sqz holes @ 297'. TOOH. Establish circ down csg & out bradenhead w/40 bbl wtr. Plug #6: pump 110 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. (Jimmy Morris, BLM on location for plugging). Well plugged and abandoned 8-12-97.