

(October 1990)

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FOR APPROVED
O&B NO. 1004-0137
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL:		OIL WELL ☐	GAS WELL ☒	DRY ☐	Other _____
b. TYPE OF COMPLETION:					
NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. REVR. ☐	Other _____
2. NAME OF OPERATOR Texakoma Oil & Gas Corporation					
3. ADDRESS AND TELEPHONE NO. (972) 701-9106 5400 LBJ Fwy - Suite 500-One Lincoln Centre-Dallas, TX 75240					
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1820' FSL & 2205' FWL At top prod. interval reported below Same as Above At total depth Same as Above					
14. PERMIT NO.			DATE ISSUED 8/31/98		
15. DATE SPUDDED 11/16/98		16. DATE T.D. REACHED 11/24/98		17. DATE COMPL. (Ready to prod.) 1/19/99	
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 5825' RKB		19. ELEV. CASINGHEAD 5820			
20. TOTAL DEPTH, MD & TVD 1845' MD		21. PLUG, BACK T.D., MD & TVD 1820' MD		22. IF MULTIPLE COMPL., HOW MANY*	
23. INTERVALS DRILLED BY → 0-1845'				ROTARY TOOLS CABLE TOOLS	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 1576'-1584', 1646'-1650', 1652'-1658', 1774'-1782', 1784'-1796', Fruitland Coal					25. WAS DIRECTIONAL SURVEY MADE NO
26. TYPE ELECTRIC AND OTHER LOGS RUN Dual Induction, Microlog, Neutron-LithoDensity, Gamma Ray, Caliper, CBL					27. WAS WELL CORED No
28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8"/J-55	- 24	121'	12 1/4"	95 Sxs"B" w/2%CaCl -Surface	None
5 1/2"/J-55	15.5	183'	7 7/8"	Surface:190Sxs"C" Lite +	None
		2		50Sxs "B" + .25 pps Celloflake	
29. LINER RECORD				30. TUBING RECORD	
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	
				2 7/8"	1792'
31. PERFORATION RECORD (Interval, size and number)				32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
1576'-1584', 0.45 EHD, 48 Holes				DEPTH INTERVAL (MD)	
1646'-1650', 0.45 EHD, 24 Holes				1774'-1796'	
1652'-1658', 0.45 EHD, 36 Holes					
1774'-1782', 0.45 EHD, 48 Holes				1576'-1658'	
1784'-1796', 0.45 EHD, 72 Holes					
				AMOUNT AND KIND OF MATERIAL USED	
				20# Delta;51000g., 150m# 12/20	
				BradySand, Sandwedge	
				20# Delta;19,011g, 13m# 12/20	
				BradySand, Sandwedge	
33. PRODUCTION					
DATE FIRST PRODUCTION 1/19/99		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Pumping - 1 3/4" insert pump			WELL STATUS (Producing or shut-in) Producing
DATE OF TEST 1/21/99	HOURS TESTED 24	CHOKE SIZE NA	PROD'N. FOR TEST PERIOD →	OIL—BBL. 0	GAS—MCF. 20
					WATER—BBL. 74
					GAS-OIL RATIO NA
FLOW. TUBING PRBS.	CASING PRESSURE 20	CALCULATED 24-HOUR RATE →	OIL—BBL. 0	GAS—MCF. 20	WATER—BBL. 74
					OIL GRAVITY-API (CORR.) NA
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Vented - waiting on pipeline					TEST WITNESSED BY Brad Salzman
35. LIST OF ATTACHMENTS Acoustic Cement Bond Log					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.					
SIGNED <i>APR Kendrick</i>		TITLE <i>Drilling Manager</i>		DATE <i>1/26/99</i>	

*(See Instructions and Spaces for Additional Data on Reverse Side)

JAN 27 1999

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMCCD

ADMINISTRATIVE DISTRICT OFFICE
S.M.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38.

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Coals within Fruitland	1576'	1584'	Coal: Black, vitreous, cleated,	Basal Coal	1774'	1774'
	1646'	1650'	Coal: some visible desorption			
	1652'	1658'	Coal: "			
	1774'	1782	Coal: "			
	1784'	1796'	Coal: "			