

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
BLM

MAY 19 1999 PM 12:31

Sundry Notices and Reports on Wells

070 FARMINGTON, NM

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

RECEIVED  
MAY 24 1999

OIL CON. DIV.  
DIST. 3

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1505' FSL, 790' FWL, Sec. 35, T-31-N, R-12-W, NMPM

5. Lease Number  
SF-078120A

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name & Number  
Federal G #1M

9. API Well No.  
30-045-29735

10. Field and Pool  
Blanco MV/Basin DK

11. County and State  
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other - Spud, casing, and cement	

13. Describe Proposed or Completed Operations

5-8-99 MIRU. Spud well @ 6:00 pm 5-8-99. Drill to 245'. Circ hole clean. TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 csg, set @ 241'. Cmt'd w/180 sx Class "B" neat cmt w/3% calcium chloride, 0.25 pps Flocele (212 cu ft). Circ 16.5 bbl cmt to surface. WOC.

5-9-99 NU BOP. PT BOP & csg to 600 psi/30 min, OK. Drilling ahead.

5-10-99 Drill to intermediate TD @ 2570'. Circ hole clean. TOOH. TIH w/62 jts 7" 23# J-55 csg, set @ 2563'. Cmt'd w/290 sx Class "B" neat cmt w/3% sodium metasilicate, 0.25 pps Flocele, 5 pps Gilsonite (844 cu ft). Tailed w/90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 0.25 pps Flocele, 5 pps Gilsonite (124 cu ft). Circ 53 bbl cmt to surface. WOC. NU BOP. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 5/18/99  
vkh

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON FIELD OFFICE  
BY Swm

NMOC