

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals

RECEIVED
BLM

99 JAN -6

070 FALCON

Designation and Serial No.

SF-078319-A

6. If Indian, Allottee or Tribe Name

AM 10: 02

7. If Unit or CA, Agreement Designation

BLM DISTRICT, NM

8. Well Name and No.

Barrett LS

#1B

9. API Well No.

3004529773

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

SAN JUAN

NEW MEXICO

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention:

Gail M. Jefferson

3. Address and Telephone No.

P.O. BOX 800 DENVER, COLORADO 80201

(303) 830-6157

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1820' FNL

840' FWL

Sec. -30 T 31N R .9W

UNIT F

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud and Set Sundry

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU spud 12.25" surface hole on 11/27/98 at 17:30 hrs. Drilled to 282'. Set 9.625" 36# K-55 surface pipe at 268'. Cemented with 213 sxs Class B cement. Cemented pipe to surface circulated 75 sxs Clabbered mud and cmt and 25 sxs of good cement to surface with no fall back. Pressure tested to 1200#.

Drill a 8.750" intermediate hole on 12/1/98 at 17:00 hrs. Drilled to 3465'. Set 7" 20 and 23# K-55 intermediate casing at 3461'. Cemented with 150 sxs Class B lead and 290 sxs Class B tail. Stage one circulated poorly and did not circ cmt. Stage two had good circulation and circulated 25 bbls of good cement to surface. Pressure tested to 1200#.

Drill a 6.250" hole to 6,024' on 12/4/98. Set 4.50" 10.5# J-55 Production liner at 6024'. Cemented with 306 sxs Class B cement. Circulated 53 sxs good cement to surface. Pressure tested to 1200#

Ran CBL TOC @ 3253' at liner top.

Rig released 16:00 hrs on 12/4/98.

14. I hereby certify that the foregoing is true and correct

Signed

Gail M. Jefferson

Title

Sr. Admin. Staff Asst.

Date

12-19-1998

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

JAN 06 1999

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instructions on Reverse Side

NMOCD