

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

OCT - 4 1999

OIL CON. DIV.
DIST. 3

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit N, 909' FSL & 1583' FWL
Section 22, T32N, R9W

5. Lease Designation and Serial No.

SF-079341

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 32 Fed Com 22

8. Well Name and No.

SJ 32 Fed Com 22 #

9. API Well No.

30-045029788

10. Field and Pool, or exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud Report
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled: give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/25/99 MIRU Key Energy #53. Spud 12-1/4" hole @ 2000 hrs 9/26/99. Drilled ahead to 350'. Circ. hole. RIH w/9-5/8" 36#, K-55 casing and set @ 345'. RU BJ to cement. Pumped 195 sx (234 cf) Class H cement w/2% CaCl2. 1/4#/sx Cello-flake mixed at 15.6 ppg w/1.20 yield. Circulated 8 bbls (45 cf) cement to surface. RD BJ. WOC.

NU BOPs. PT casing, rams, valves to 200 psi for 3 minutes and 1500 psi for 10 minutes. Good test.

14. I hereby certify that the foregoing is true and correct

Signed Patsy Clugston Title Regulatory Assistant Date 9/28/99

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

RECEIVED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

NMOCD

FARMINGTON FIELD OFFICE
BY [Signature]