

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPlicate

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 DIS-3 599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit F, 1475' FNL & 1470' FWL
Section 33, T32N, R7W

5. Lease Designation and Serial No.

SF-078543

6. If Indian, Allottee or Tribe Name

44

7. Unit or CA, Agreement Designation

San Juan 32-7 Unit

8. Well Name and No.

SJ 32-7 Unit #91

9. API Well No.

30-045-29877

10. Field and Pool, or exploratory Area

S. Los Pinos
Fruitland Sands PC

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud Report
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/23/99

MIRU Key Energy #37. Spud 12-1/4" hole @ 2130 hrs 5/23/99. Drilled ahead to 282'. Circ. hole. RIH w/8-5/8" 24#, K-55 casing and set @ 277'. RU BJ to cement. Pumped 10 bbs mud clean and 10 bbls water spacer ahead of 205 sx (246 cf) C1 H cement w/2% CaCl2 & 1/4#/sx Cello-flake, mixed at 15.6 ppg w/1.20 yield, rate 3 bpm @ 100 psi. Dropped wood plug & displace w/16 bbls water. Circulated 8 bbls (45 cf) cement to surface. WOC. NU WH & BOP & lines. PT casing, blind rams, valves to 200 psi 3 min and 2000 psi for 10 minutes. Good test.

APD/ROW

14. I hereby certify that the foregoing is true and correct

Signed

Patsy Clugston

Title

Regulatory Assistant

Date

5/25/99

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

NMOC

SMV