

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit G, 1630' FNL & 1475' FEL
Section 27, T32N, R7W

5. Lease Designation and Serial No.

SF-078472

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 32-7 Unit

8. Well Name and No.

SJ 32-7 Unit #90

9. API Well No.

30-045-29879

10. Field and Pool, or exploratory Area

S. Los Pinos Fruitland
Sands PC, Ext.

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud Report
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/18/99

MIRU Key Energy #37. Spud 12-1/4" hole @ 1730 hrs on 5/18/99. Drilled ahead to 348'. RIH w/8-5/8" 24#, K-55 ST&C casing and set @ 279'. RU BJ to cement. Pumped 10 bbls mud clean & 10 bbl water spacer ahead of 205 sx (247 cf) C1 H cement w/2% CaCl₂, 1/4#/sx Cello-flake, mixed at 15.6 ppg w/1.20 yield. Dropped wood plug & displaced with 16 bbls water. Had 10 bbls (56 cf) cement circulated to surface. WOC.

NU WH & NU BOP. PT blind rams, caing and manifold to 200 psi for 3 min, then to 2000 psi for 10 min. Good test.

APD / ROW

14. I hereby certify that the foregoing is true and correct

Signed

Rosalyn Clugston

Title

Regulatory Assistant

Date

5/20/99

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

NMOC

MAY 24 1999