

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1680' FSL, 1750' FWL, Sec. 24, T-32-N, R-7-W, NMPM, San Juan County

API # (assigned by OCD)

30-045-29949

5. Lease Number

Fee

6. State Oil & Gas Lease #

7. Lease Name/Unit Name

Allison Unit


8. Well No.

#71

9. Pool Name or Wildcat

S. Los Pinos FT Snd PC

10. Elevation:



Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other -

13. Describe Proposed or Completed Operations

- 5-9-00 MIRU. ND WH. NU BOP. TIH w/CIBP, set @ 3360'. TIH w/4 1/2" pkr, set @ 3350'. PT CIBP to 2000 psi/15 mins, OK. Rls pkr & TOOH. SDON.
- 5-10-00 (Verbal approval from Charlie Perrin, OCD, to squeeze). TIH w/cmt ret, set @ 3255'. Sqz perfs @ 3309-3337' w/75 sx Class "B" w/.4% Halad-344, 2% calcium chloride (89 cu ft). Reve circ. TOOH. TIH w/bit. SDON.
- 5-11-00 D/O cmt ret @ 3255'. D/O cmt to CIBP @ 3360'. Circ hole clean. PT csg & sqz to 500 psi/15 mins, OK. D/O CIBP @ 3360'. Blow well & CO to CIBP @ 3480'. SDON.
- 5-12-00 Blow well clean. Tag CIBP @ 3480'. Push to 3707'. Blow well clean. TOOH w/bit. TIH w/cmt ret, set @ 3530'. Sqz perfs @ 3540-3670' w/50 sx Class "B" w/.4% Halad-344, 2% calcium chloride. TIH w/4 1/2" 10.5# csg patch, set across sqz holes @ 3303-3343'. TOOH. SDON.
- 5-13-00 Frac PC perfs @ 3398-3473' w/626 bl 20# lnr gel, 200,000# 20/40 Brady snd, 896,524 SCF N2. Flow back well.
- 5-14/17-00 Flow back well.
- 5-18-00 TIH w/fishing tools. Tag up @ 3270'. CO to fish @ 3303'. Blow well clean.
- 5-19-00 Fish csg patch & jar loose. TOOH w/30' of csg patch. Bottom 10' left in hole. Blow well clean. SDON.
- 5-20-00 TIH, spear 4 1/2" csg patch. Jar loose. TOOH w/bottom 10' of csg patch. TIH w/bit. Blow well & CO to PBTD @ 3510'.
- 5-22-00 Blow well & CO to PBTD @ 3510'. TOOH w/bit. ND BOP. NU WH. RD. Rig released.

SIGNATURE

Reggie Cole

Regulatory Supervisor June 13, 2000

TLW

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERRIN

DEPUTY OIL & GAS INSPECTOR, DIST. 3

JUN 15 2000

Approved by

Title

Date