

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Koch Exploration Company

3. Address and Telephone No.

P.O. Box 489 Aztec, New Mexico 87410 (505) 334-9111

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

S13, T31N, R10W (J)
1715' FSL & 1610' FEL

5. Lease Designation and Serial No.
NM-014110

6. If Indian, Allottee or Tribe Name

NA

7. If Unit or C.A. Agreement Designation

NA

8. Well Name and No.

Walker 113

9. API Well No.

30-045-30279

10. Field and Pool, or Exploratory Area

Blanco Mesa Verde

11. County or Parish, State

San Juan County
New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Intermediate Casing & Cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Compelled Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 8 3/4" hole and ran 7", 20#, J-55 new casing, landed @ 3632' KB. DV Tool @ 3096' KB. Cemented on 11/20/00. 1st stage lead with 50 sacks of 9.5# LiteCRETE, (70% excess), Yield 2.51, with 1/2#/sack Celloflake, tailed with 50 sacks of 15.8#, Yield 1.19 Class H cement. Circulated 10 Bbl's of cement to surface. Opened DV Tool and circulated for 4 hours. 2nd Stage lead with 285 sacks of 9.5# LiteCRETE, (70% excess), Yield 2.51, with 1/2#/sack Celloflake, tailed with 85 sacks of 15.8#, Yield 1.19 Class H cement. Circulated 27 Bbl's of cement to surface. WOC 16 hours. Pressure tested casing to 1000#. Held OK.

I hereby certify that the foregoing is true and correct

Signed 
(This space for Federal or State office use)

Title Operations Manager

Date

Approved by

Date

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD
11/21/00

DEC 19 2000

FARMINGTON FIELD OFFICE

BY

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or