

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1405' FSL, 930' FWL, Sec. 28, T-32-N, R-6-W, NMPM L

5. Lease Number
SF-081155

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name
Allison Unit

8. Well Name & Number
Allison Unit #52B

9. API Well No.
30-045-30367

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input checked="" type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

It is intended to alter the casing depths and cement of the subject well.

Revisions:

Mud Program:

Interval	Type	Weight	Fluid Loss
0-200'	Spud	8.4-9.0	No control
200-4015'	LSND	8.4-9.0	No control
4015-6365'	Air/Mist	n/a	n/a

Casing Program:

Hole Size	Depth Interval	Casing Size	Weight	Grade
12 1/4"	0-200'	9 5/8"	32.3#	H-40
8 3/4"	0-4015'	7"	20.0#	J-55
6 1/4"	3915-6365'	4 1/2"	10.5#	J-55

Cementing Program:

9 5/8" surface casing - 159 sx Class "B" cement with 0.25 pps Flocele and 3% calcium chloride (188 cu.ft. of slurry, 200% excess to circulate to surface).
 7" intermediate casing - lead w/423 sx 50/50 Class "G"/Trinity Light with 2.5% sodium metasilicate, 2% calcium chloride, 10 pps Gilsonite, 0.5 pps Flocele. Tail with 90 sx Class "G" 50/50 poz w/2% gel, 2% calcium chloride, 5 pps Gilsonite, 0.1% antifoam and 0.25 pps Flocele (1208 cu.ft. of slurry, 100% excess to circulate to surface).
 7" intermediate casing alternative two stage: Stage collar at 3021'. First stage: cement w/234 sx 50/50 Class "G" poz w/2% gel, 2% calcium chloride, 5 pps Gilsonite, 0.1% antifoam and 0.25 pps Flocele. Second stage: w/352 sx 50/50 Class "G"/Trinity Light with 2.5% sodium metasilicate, 2% calcium chloride, 10 pps Gilsonite, 0.5 pps Flocele (1208 cu.ft. of slurry, 100% excess to circulate to surface).
 4 1/2" production liner - cement with 245 sx Class "G" 50/50 poz w/4.5% gel, 0.25 pps Flocele, 5 pps Gilsonite, 0.25% fluid loss, 0.1% retardant (352 cu.ft., 50% excess to circulate liner).

14. I hereby certify that the foregoing is true and correct.

Signed Peggy Cale Title Regulatory Supervisor Date 11/8/00
TLW

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date 1/12/01

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD