State of New Mexico Energy, Minerals and Natural Resources Department Oil Conservation Division

	3 0 7	# (aggigmed her OCD)
	API	# (assigned by OCD) 30-045-30561
I. Type of Well	5.	Lease Number
GAS		Fee
	6.	State Oil&Gas Lease #
2. Name of Operator	7.	Lease Name/Unit Name
BURLINGTON		
RESOURCES OIL & GAS COMPANY		Stull
Administration of Openshop	8.	Well No. #2
. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	
FO BOX 4209, Parmingcom, Int. 0/499 (303, 320 9/00	٥.	Basin Dakota/
		Wildcat Mancos
. Location of Well, Footage, Sec., T, R, M		Elevation:
1630'FSL, 1070'FWL, Sec.10, T-32-N, R-10-W, NMPM, San Juan	n County	
Type of Submission Type of Action		
Notice of Intent Abandonment Char	nge of Pla	ans
Recompletion New	Construc	tion
	er Shut o	Fracturing ff
Final Abandonment Altering Casing Con		
X_ Other - casing & cement		-
4-25-01 TIH w/179 jts 4-1/2" 10.5# J-55 ST&C csg, set Litecrete w/0.11% dispersant, 0.50% fluid l		Cmtd w/186 ev
<pre>w/183 sx Class Class "G" 50/50 poz w/5% gel 5 pps gilsonite, 0.15% dispersant, 0.10% re (263 cu ft). ND BOP. NU WH. RD. Rig release</pre>	, 0.25 pp tarder, 0	cu ft). Tail s cellophane,
w/183 sx Class Class G" 50/50 poz w/5% gel 5 pps gilsonite, 0.15% dispersant, 0.10% re (263 cu ft). ND BOP. NU WH. RD. Rig release	, 0.25 pp tarder, 0	cu ft). Tail s cellophane,
w/183 sx Class Class "G" 50/50 poz w/5% gel 5 pps gilsonite, 0.15% dispersant, 0.10% re (263 cu ft). ND BOP. NU WH. RD. Rig release Relakt Cement Tals	, 0.25 pp tarder, 0 d. MAY 20	cu ft). Tail s cellophane, .25% fluid loss
w/183 sx Class "G" 50/50 poz w/5% gel 5 pps gilsonite, 0.15% dispersant, 0.10% re (263 cu ft). ND BOP. NU WH. RD. Rig release Regulatory Supervise	, 0.25 pp tarder, 0 d. MAY 20	cu ft). Tail s cellophane, .25% fluid loss
w/183 sx Class "G" 50/50 poz w/5% gel 5 pps gilsonite, 0.15% dispersant, 0.10% re (263 cu ft). ND BOP. NU WH. RD. Rig release Regulatory Supervis (This space for State Use)	O.25 pp tarder, 0 d. MAY 20	cu ft). Tail s cellophane, .25% fluid loss
w/183 sx Class Class "G" 50/50 poz w/5% gel 5 pps gilsonite, 0.15% dispersant, 0.10% re (263 cu ft). ND BOP. NU WH. RD. Rig release Refirt Cement Take	MAY 20	cu ft). Tail s cellophane, .25% fluid loss