

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-045-30889
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator ENERGEN RESOURCES CORPORATION		6. State Oil & Gas Lease No.
3. Address of Operator 2198 Bloomfield Highway, Farmington, NM 87401		7. Lease Name or Unit Agreement Name: Culpepper Martin
4. Well Location Unit Letter <u>G</u> : <u>1900</u> feet from the <u>North</u> line and <u>2200</u> feet from the <u>East</u> line Section <u>07</u> Township <u>31N</u> Range <u>12W</u> NMPM County <u>San Juan</u>		8. Well No. 2B
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 5866' GR		9. Pool name or Wildcat Blanco Mesaverde

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12/20/01 TD: 5097'. Ran 54 jts. 4-1/2" 10.5# J-55 ST&C casing, set @ 5008'. TOL: 2560'.
RU Halliburton. Cement with 300 sks 50/50 Class B poz, 5#/sk gilsonite, 1/4#/sk flocele, 2% gel, 0.5% Halad-9, 0.2% CFR-3, 0.1% HR-5 (396 cu.ft.). Plug down @ 11:30pm 12/21/01. Circulate 65 sks cement to surface. TOC: 2560'. RD Halliburton. ND BOP. Rig released 12/21/01.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vicki Donaghey TITLE Production Assistant DATE 12/26/01

Type or print name Vicki Donaghey

Telephone No. 505-325-6800

(This space for State use)

SPECIAL SIGNED BY CHARLES T. PETERSON

PROPERTY OF STATE OF NEW MEXICO

DEC 28 2001

APPROVED BY _____ TITLE _____ DATE _____

Conditions of approval, if any: