UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	tices and Reports on Well	5.	Lease Number
			NMSF078040A If Indian, All. or
Type of Well	·	6.	Tribe Name
GAS			IIIDe Namo
		7.	Unit Agreement Name
Name of Operator			
RURI INGTON			
RESOURCES OIL	L & GAS COMPANY		
		8.	Well Name & Number Childers #3M
Address & Phone No. of Oper	eator	9.	
PO Box 4289, Farmington, NM	M 87499 (505) 326-9700	۶.	30-045-30907
. Location of Well, Footage, Se	Sec., T, R, M	10.	Field and Pool
880'FSL, 1925'FEL, Sec.1, T	-31-N, R-11-W, NMPM		Blanco MV/Basin DK
, , , , , , , , , , , , , , , , , , , ,		11.	County and State San Juan Co, NM
			San Juan Co, MM
. CHECK APPROPRIATE BOX TO I	NDICATE NATURE OF NOTICE	. REPORT, OTHER	DATA
Type of Submission	Type of Ac	tion	
Notice of Intent	Abandonment _	Change of Pl	
	Recompletion	New Construc	tion Exacturing
X Subsequent Report	Plugging Back Casing Repair	Non-Routine	fracturing
	Casing Repair _ Altering Casing _	Conversion t	o Injection
Final Abandonment	X Other -	_	-
. Describe Proposed or Cor	mpleted Operations		
	-		
77 77 77 77 77 77 77 77 77 77 77 77 77	ring to 7340' Ran (BL-GR-CCL @ 732	8-700' and GR-CCL
3/5/02 RU W/L. TIH w/ga	auge ring to 7340'. Ran C	. TOC on / e s	100 . KD 11/11.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approva	auge ring to 7340'. Ran C ce. TOC on 4-1/2" @ 4940' al from Steve Mason, BLM,	. TOC on / e s	100 . KD 11/11.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approve	auge ring to 7340'. Ran Coce. TOC on 4-1/2" @ 4940'al from Steve Mason, BLM,	no need to rem	nediate 7" cmt,
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approve remidate 4-1	auge ring to 7340'. Ran Coce. TOC on 4-1/2" @ 4940'al from Steve Mason, BLM, /2" cmt).	no need to rem	nediate 7" cmt,
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approver remidate 4-1 4/10/02 TIH w/CIBP, set TIH w/cmt re	auge ring to 7340'. Ran Coce. TOC on 4-1/2" @ 4940'al from Steve Mason, BLM,/2" cmt). t @ 5480'. PT CIBP to 410t, set @ 3590'. PT tbg to	no need to rem	nediate 7" cmt, sqz hole @ 3641'. Sqz w/200 sxs Type
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approver remidate 4-1, 4/10/02 TIH w/CIBP, set TIH w/cmt ret "3" neat cm	auge ring to 7340'. Ran Coce. TOC on 4-1/2" @ 4940' al from Steve Mason, BLM, /2" cmt). t @ 5480'. PT CIBP to 410t, set @ 3590'. PT tbg to t. SDON.	no need to rem O psi, OK. Perf 3000 psi, OK.	nediate 7" cmt, sqz hole @ 3641'. Sqz w/200 sxs Type
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approva remidate 4-1 4/10/02 TIH w/CIBP, se TIH w/cmt re "3" neat cm 4/11/02 TIH w/mill, tag	auge ring to 7340'. Ran Commerce. TOC on 4-1/2" @ 4940' al from Steve Mason, BLM,/2" cmt). t @ 5480'. PT CIBP to 410 t, set @ 3590'. PT tbg to t. SDON. g cmt @ 3560'. Mill out omt to 3597'. TOOH w/mill.	no need to rem O psi, OK. Perf 3000 psi, OK.	nediate 7" cmt, sqz hole @ 3641'. Sqz w/200 sxs Type
3/5/02 RU W/L. TIH w/ga @ 700'-surfac @ 700'-surfac semidate 4-1 4/10/02 TIH w/CIBP, se TIH w/cmt re "3" neat cm 4/11/02 TIH w/mill, ta Drill hard co	auge ring to 7340'. Ran Coe. TOC on 4-1/2" @ 4940' al from Steve Mason, BLM, /2" cmt). t @ 5480'. PT CIBP to 410 t, set @ 3590'. PT tbg to t. SDON. g cmt @ 3560'. Mill out of mt to 3597'. TOOH w/mill.	no need to rem O psi, OK. Perf 3000 psi, OK. cmt to 3590'. Mi	ediate 7" cmt, sqz hole @ 3641'. Sqz w/200 sxs Type lll cmt ret @ 3590'. S597'. Drill hard
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approvation of the control of the contro	auge ring to 7340'. Ran Commerce. TOC on 4-1/2" @ 4940' al from Steve Mason, BLM, /2" cmt). t @ 5480'. PT CIBP to 410 t, set @ 3590'. PT tbg to t. SDON. g cmt @ 3560'. Mill out community and to 3597'. TOOH w/mill. Circ hole clean. SDON.	no need to rem no psi, OK. Perf 3000 psi, OK. cmt to 3590'. Mi TIH w/bit to 3	nediate 7" cmt, sqz hole @ 3641'. sqz w/200 sxs Type lll cmt ret @ 3590'. 3597'. Drill hard nole to 500 psi, OK.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approvation of the control of the contro	auge ring to 7340'. Ran Commerce. TOC on 4-1/2" @ 4940' al from Steve Mason, BLM, /2" cmt). t @ 5480'. PT CIBP to 410 t, set @ 3590'. PT tbg to t. SDON. g cmt @ 3560'. Mill out community and to 3597'. TOOH w/mill. Circ hole clean. SDON. to 3642'. TIH to CIBP @ Pap GP/CCL/CBL @ 4940-295	no need to rem no psi, OK. Perf 3000 psi, OK. mut to 3590'. Mi TIH w/bit to 3 5480'. PT sqz 1	nediate 7" cmt, sqz hole @ 3641'. Sqz w/200 sxs Type ll cmt ret @ 3590'. 3597'. Drill hard hole to 500 psi, OK. '. Perf sqz hole @
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approva remidate 4-1 4/10/02 TIH w/CIBP, set TIH w/cmt ret "3" neat cm 4/11/02 TIH w/mill, tac Drill hard comt to 3635' 4/12/02 Drill hard cmt TOOH w/bit. 4236'. TIH w	auge ring to 7340'. Ran Comment of the comment of t	no need to rem no psi, OK. Perf 3000 psi, OK. mt to 3590'. Mi TIH w/bit to 3 5480'. PT sqz 1 33', TOC @ 3604' nt sqz w/200 sxs	rediate 7" cmt, E sqz hole @ 3641'. Sqz w/200 sxs Type Ell cmt ret @ 3590'. B597'. Drill hard Hole to 500 psi, OK. Y. Perf sqz hole @ S Type "3" neat cmt.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approva- remidate 4-1, 4/10/02 TIH w/CIBP, ser TIH w/cmt re- "3" neat cm 4/11/02 TIH w/mill, tag Drill hard coment to 3635' 4/12/02 Drill hard cmt TOOH w/bit. 4236'. TIH w/mill. CO	auge ring to 7340'. Ran Comment of the comment of t	no need to rem no psi, OK. Perf 3000 psi, OK. emt to 3590'. Mi TIH w/bit to 3 5480'. PT sqz h 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO	Rediate 7" cmt, E sqz hole @ 3641'. Sqz w/200 sxs Type Ill cmt ret @ 3590'. B597'. Drill hard Hole to 500 psi, OK. '. Perf sqz hole @ S Type "3" neat cmt. cmt to 4236'. TIH
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approva remidate 4-1 4/10/02 TIH w/CIBP, se TIH w/cmt re "3" neat cm 4/11/02 TIH w/mill, tac Drill hard co cmt to 3635' 4/12/02 Drill hard cmt TOOH w/bit. 4236'. TIH w Circ 1.5 bbl 4/15/02 TIH w/mill. CO	auge ring to 7340'. Ran Comment to 4182'. Mill cmt to 4182'. Mill cmt to 4182'. Mill cmt to 4182'. Comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Comment to 4182'. Comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Comment to 4182'. Comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Comment to 4182'. Mill comment to 4182'. Comment to 4	no need to rem no need to rem no psi, OK. Perf 3000 psi, OK. mut to 3590'. Mi TIH w/bit to 3 5480'. PT sqz h 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO OK. TOOH w/mill	rediate 7" cmt, sqz hole @ 3641'. sqz w/200 sxs Type lll cmt ret @ 3590'. 3597'. Drill hard hole to 500 psi, OK. '. Perf sqz hole @ s Type "3" neat cmt. cmt to 4236'. TIH
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approva remidate 4-1, 4/10/02 TIH w/CIBP, se TIH w/cmt re "3" neat cm 4/11/02 TIH w/mill, tac Drill hard co cmt to 3635' 4/12/02 Drill hard cmt TOOH w/bit. 4236'. TIH w Circ 1.5 bbl 4/15/02 TIH w/mill. CO	auge ring to 7340'. Ran Comment of the comment of t	no need to rem no need to rem no psi, OK. Perf 3000 psi, OK. mut to 3590'. Mi TIH w/bit to 3 5480'. PT sqz h 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO OK. TOOH w/mill	rediate 7" cmt, sqz hole @ 3641'. sqz w/200 sxs Type lll cmt ret @ 3590'. 3597'. Drill hard hole to 500 psi, OK. '. Perf sqz hole @ s Type "3" neat cmt. cmt to 4236'. TIH
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approvation remidate 4-1, 4/10/02 TIH w/CIBP, set TIH w/cmt ret "3" neat cm 4/11/02 TIH w/mill, tag Drill hard cm cmt to 3635' 4/12/02 Drill hard cmt TOOH w/bit. 4236'. TIH w Circ 1.5 bbl 4/15/02 TIH w/mill. CO to CIBP @ 54 4/25/02 TIH w/mill. Mi	auge ring to 7340'. Ran Comment of the state	no need to rem no psi, OK. Perf 3000 psi, OK. emt to 3590'. Mi TIH w/bit to 3 5480'. PT sqz h 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO OK. TOOH w/mill h junk to 7280'	Rediate 7" cmt, E sqz hole @ 3641'. Sqz w/200 sxs Type Ill cmt ret @ 3590'. B597'. Drill hard Hole to 500 psi, OK. '. Perf sqz hole @ S Type "3" neat cmt. cmt to 4236'. TIH . Blow well & CO.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approvation remidate 4-1, 4/10/02 TIH w/CIBP, set TIH w/cmt ret "3" neat cm 4/11/02 TIH w/mill, tag Drill hard cm cmt to 3635' 4/12/02 Drill hard cmt TOOH w/bit. 4236'. TIH w Circ 1.5 bbl 4/15/02 TIH w/mill. CO to CIBP @ 54 4/25/02 TIH w/mill. Mi	auge ring to 7340'. Ran Comment to 4182'. Mill cmt to 4182'. Mill cmt to 4182'. Mill cmt to 4182'. Comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Comment to 4182'. Comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Comment to 4182'. Comment to 4182'. Mill comment to 4182'. Mill comment to 4182'. Comment to 4182'. Mill comment to 4182'. Comment to 4	no need to rem no psi, OK. Perf 3000 psi, OK. emt to 3590'. Mi TIH w/bit to 3 5480'. PT sqz h 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO OK. TOOH w/mill h junk to 7280'	Rediate 7" cmt, E sqz hole @ 3641'. Sqz w/200 sxs Type Ill cmt ret @ 3590'. B597'. Drill hard Hole to 500 psi, OK. '. Perf sqz hole @ S Type "3" neat cmt. cmt to 4236'. TIH . Blow well & CO.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approvation of the content of the conten	auge ring to 7340'. Ran Comment of the state	no need to rem no psi, OK. Perf 3000 psi, OK. emt to 3590'. Mi TIH w/bit to 3 5480'. PT sqz 1 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO OK. TOOH w/mill h junk to 7280' le under DHC700	Rediate 7" cmt, E sqz hole @ 3641'. Sqz w/200 sxs Type Ill cmt ret @ 3590'. B597'. Drill hard Hole to 500 psi, OK. '. Perf sqz hole @ S Type "3" neat cmt. cmt to 4236'. TIH . Blow well & CO.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approvation remidate 4-1, 4/10/02 TIH w/CIBP, set TIH w/cmt ret "3" neat cm 4/11/02 TIH w/mill, tag Drill hard cmt cmt to 3635' 4/12/02 Drill hard cmt TOOH w/bit. 4236'. TIH w Circ 1.5 bbl 4/15/02 TIH w/mill. CO to CIBP @ 54 4/25/02 TIH w/mill. Mill Well will produce as a	auge ring to 7340'. Ran Comment of the state	no need to rem no psi, OK. Perf 3000 psi, OK. emt to 3590'. Mi TIH w/bit to 3 5480'. PT sqz 1 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO OK. TOOH w/mill h junk to 7280' le under DHC700	Rediate 7" cmt, E sqz hole @ 3641'. Sqz w/200 sxs Type Ill cmt ret @ 3590'. B597'. Drill hard Hole to 500 psi, OK. '. Perf sqz hole @ S Type "3" neat cmt. cmt to 4236'. TIH . Blow well & CO.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approvation remidate 4-1, 4/10/02 TIH w/CIBP, set TIH w/cmt ret "3" neat cm 4/11/02 TIH w/mill, tag Drill hard cmt cmt to 3635' 4/12/02 Drill hard cmt TOOH w/bit. 4236'. TIH w Circ 1.5 bbl 4/15/02 TIH w/mill. CO to CIBP @ 54 4/25/02 TIH w/mill. Mill Well will produce as a	auge ring to 7340'. Ran Coe. TOC on 4-1/2" @ 4940' al from Steve Mason, BLM, /2" cmt). t @ 5480'. PT CIBP to 410t, set @ 3590'. PT tbg to t. SDON. g cmt @ 3560'. Mill out of mt to 3597'. TOOH w/mill. Circ hole clean. SDON. to 3642'. TIH to CIBP @ Ran GR/CCL/CBL @ 4940-293'/cmt ret, set @ 4182'. Crs cmt out annulus. SDON. cmt to 4182'. Mill cmt to 4182'. Mill cmt to 4182'. Mill cmt to 4182'. Mill cmt to 4182'. PT sqz to 500 psi, @ 11 out CIBP @ 5480'. Pusimesaverde/Dakota comming the foregoing is true and	no need to rem no psi, OK. Perf 3000 psi, OK. emt to 3590'. Mi TIH w/bit to 3 5480'. PT sqz 1 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO OK. TOOH w/mill h junk to 7280' le under DHC700 correct.	sqz hole @ 3641'. Sqz w/200 sxs Type Ill cmt ret @ 3590'. S597'. Drill hard hole to 500 psi, OK. '. Perf sqz hole @ s Type "3" neat cmt. cmt to 4236'. TIH . Blow well & CO. az.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approvation remidate 4-1, 4/10/02 TIH w/CIBP, set TIH w/cmt ret "3" neat cm 4/11/02 TIH w/mill, tag Drill hard cmt cmt to 3635' 4/12/02 Drill hard cmt TOOH w/bit. 4236'. TIH w Circ 1.5 bbl 4/15/02 TIH w/mill. CO to CIBP @ 54 4/25/02 TIH w/mill. Mill Well will produce as a	auge ring to 7340'. Ran Comment of the state	no need to rem no psi, OK. Perf 3000 psi, OK. emt to 3590'. Mi TIH w/bit to 3 5480'. PT sqz 1 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO OK. TOOH w/mill h junk to 7280' le under DHC700 correct.	sqz hole @ 3641'. Sqz w/200 sxs Type Ill cmt ret @ 3590'. S597'. Drill hard hole to 500 psi, OK. '. Perf sqz hole @ s Type "3" neat cmt. cmt to 4236'. TIH . Blow well & CO. az.
3/5/02 RU W/L. TIH w/ga @ 700'-surfac 3/13/02 (Verbal approvaremidate 4-1, 4/10/02 TIH w/CIBP, set TIH w/cmt remail words and the set of the se	auge ring to 7340'. Ran Comment of the foregoing is true and Comment of Regulato	no need to rem no psi, OK. Perf 3000 psi, OK. emt to 3590'. Mi TIH w/bit to 3 5480'. PT sqz 1 33', TOC @ 3604' nt sqz w/200 sxs ret @ 4182'. CO OK. TOOH w/mill h junk to 7280' le under DHC700 correct.	nediate 7" cmt, sqz hole @ 3641'. Sqz w/200 sxs Type ll cmt ret @ 3590'. 3597'. Drill hard hole to 500 psi, OK. ". Perf sqz hole @ s Type "3" neat cmt. cmt to 4236'. TIH . Blow well & CO. az.