

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-583

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo "B"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Mesa Gallup

11. SEC., T., R., OR BLK. AND
SURVEY OR AREA

Sec. 15, T32N, R18W

12. COUNTY OR PARISH

San Juan

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

AAA Fishing Tool Co., Inc.

3. ADDRESS OF OPERATOR

Box 234, Farmington, N. M. 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2310' fs1 330' fs1

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5696' Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐Completion ☒



(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/11/70 Ran Gamma Correlation log - perf. 2 jets/ft. 1646' - 50', 1612' - 24'.

8/13/70 S.O.F. well with 700 bbls. oil and 20,000# 20-40 sd. and 5000# 10-20 sd. Spearheaded fracture with 200 gal. 15% HCl. Breakdown press. 2700 psi, Ave. press. 2000 psi, Final 2300 psi - Dropped 15 rubber balls in two stages - pressure increased from 1750 psi to 2100 psi first 10 ball. - pressure increased from 2000 psi to 2600 psi second 5 balls. Overall average I.R. 30 BPM. Immediate S.I.P. 1100 psi. 15 min. S.I.P. 1000 psi - job complete 11:33, 8/12/70.

8/15/70 Cleaned out sand after fracture - ran 2 3/8" O.D., tubing set at 1640'. Ran rods - put well on pump.



18. I hereby certify that the foregoing is true and correct

SIGNED

Original from T. A. Dugan

TITLE

Engineer

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

DATE

10/12/70

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE : 1963-O-685229

947-485

RECEIVED
OCT 13 1970

