

- (6) After the rig moves out, all materials will be cleaned up and no adverse materials will be left on location. Any dangerous open pit will be fenced during drilling and kept closed until such time as the pit is leveled. Reserve pit will be fenced on three sides and the fourth side fenced upon removal of the rig. The trash and/or burn pit will be totally enclosed with small mesh wire.

8. Ancillary Facilities

No air strip, camp or other facilities will be built during drilling of this well.

9. Well Site Layout

- (1) EXHIBIT "G" is the Drill Pad Layout as staked with elevations, by Powers Elevation Company, Inc. of Durango, Colorado. Cuts, fills, and contours have been drafted to visualize the planned cut across the location spot and to the deepest part of the pad. Topsoil will be stockpiled per BIA/USGS specifications determined at time of pre-drill inspection.
- (2) EXHIBIT "H" is a plan diagram of the proposed rig and equipment, reserve pit, burn and trash pit, pipe racks and mud tanks. No living facilities are planned.
- (3) EXHIBIT "H" is a diagram showing the proposed rig and production facilities layout.
- (4) The reserve pits will not be lined. Steel mud tanks may be used during drilling operations.

10. Plans for Restoration

- (1) Backfilling, leveling and contouring are planned as soon as all pits have dried. Waste disposal and spoils materials will be buried or hauled away immediately after drilling is completed. If production is obtained, the unused area will be restored as soon as possible.
- (2) The soil banked material will be spread over the area. Revegetation will be accomplished by planting mixed grasses as per formula provided by the BIA. Revegetation is recommended for road area, as well as around drill pad. Area will require recontouring to avoid erosion.
- (3) Three sides of the reserve pit will be fenced during drilling operations. Prior to rig release, the reserve pit will be fenced on the fourth side to prevent livestock or wildlife from becoming entrapped; and the fencing will be maintained until leveling and cleanup is accomplished.
- (4) If any oil is on the pits and is not immediately removed after operations cease, the pit containing the oil or other adverse substances will be flagged overhead or covered with wire mesh.