

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Southland Royalty Company	8. Farm or Lease Name Decker
3. Address of Operator P. O. Drawer 570, Farmington, NM 87401	9. Well No. #4-A
4. Location of Well UNIT LETTER <u>O</u> <u>800'</u> FEET FROM THE <u>West</u> LINE AND <u>1630'</u> FEET FROM THE <u>East</u> LINE, SECTION <u>10</u> TOWNSHIP <u>32N</u> RANGE <u>12W</u> NMPM.	10. Field and Pool, or Wildcat Blanco Mesa Verde
15. Elevation (Show whether DF, RT, GR, etc.) 6098' GR	12. County San Juan


Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Casing Report</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-25-79 Set 71 joints (2785.13') of 7", 20#, K-55 8 rd casing at 2778'. Cemented with 182 sacks of Class "B", 50/50 Poz with 6% gel followed by 50 sacks of Class "B" with 2% CaCl₂. Plug down at 9:00 PM, 3-25-79.

3-28-79 Set 62 joints (2563.50') of 4 1/2", 10.5#, K-55 casing from 2636' to 5215'. Cemented with 305 sacks of 50/50, Class "B", Poz with 2% gel, 6 1/4# gilsonite per sack, 1/4# flocele per sack, .6% Halad 9 and 2% CaCl₂. Plug down at 2:45 AM, 3-29-79.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE District Production Manager DATE 3-29-79

APPROVED BY [Signature] TITLE SUPERVISOR DIST. #3 DATE MAR 30 1979

CONDITIONS OF APPROVAL, IF ANY: