Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

Revised	1-1-5

TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB	DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATIO P.O. Box 208		WELL API NO.	
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS PORCH FOR PROCOCALS TO DRILL ON TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (DO NOT USE THIS PORCH FOR PROCOCALS TO DRILL ON TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (POR MC-101) FOR SUCH PROCOCALS TO DRILL ON TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (POR MC-101) FOR SUCH PROCOCALS TO DRILL ON TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (POR MC-101) FOR SUCH PROCOCALS TO DIV.  (POR MC-101) FOR SUCH PROCOCALS  (POR MC-101) F	DISTRICT II P.O. Drawer DD, Artesia, NM 8821	ISTRICT II Santa Fe. New Mexico 87504-2088		5. Indicate Type of Lesse	
CONNOTUSE THIS FORM FOR PROPOSALS TO DELIVE APPLICATION FOR PERMY   CONNOTUSE THIS FORM FOR SUCH PROPOSALS   CONNOTUSE THIS FORM FOR CONNOTUSE THIS FORM FOR CONNOTUSE THIS FORM FOR CONNOTUSE THIS FORM FOR THE FORM FORM FOR THE FORM					
1. Tops of Well:  VINEL   VINE	( DO NOT USE THIS FORM FO DIFFERENT F (FO	R PROPOSALS TO DRILL OR TO DEEPEN	OR PLUG BACK TO A		
2 Name of Operator Southland Royalty Co.  3 Address of Operator PO Box 4289, Parmington, NM 87499  3 Po Box 4289, Parmington, NM 87499  3 Easin Fruitland Coal  4 Well Location Usit Leter : 1710 Feet Prices The North  1 Lies and 1500 Feet Prices The East Lies Section 15 Township 32N Range 12W NMPM San Juan County  10 Environ (Show whether DF, RRB, RT, CR, e.c.)  11.  12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING CHANGE PLANS CHANGE PILLING OPNS. PLUG AND ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB  OTHER:  12. Describe Proposed or Completed Operations (Clearly reas all pertinent details, and give pertinent dates, including estimated date of starting any proposed world visit 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (182 cu.ft.) circulated to surface: WOC 12 hrs. Tested 600#/30 minutes, held ok.  05-14~89 TD 2344'. Ran 54 jts. 7", 20.0#, K-55 intermediate Casing, 2332' set @ 2344'. Cemented with 390 sks. Class "B" 65/35 with 6% gel, 28 calcium chloride (182 cu.ft.) circulated to surface. WOC 12 hours. Held 1200#/30 min.  1 Descript pirity but to purify that to surface in the base of my inverted pand balled.  SOUND SIGNAL TO SURFACE OF THE PORT OF THE PROPERTY OF THE PROPE		L X OTHER (	AY1 71990	nubbaru com	
13. Address of Operator POR Box 4289, Farmington, NM 87499  1.					
Dukk Later   1710   Feet From The   North   Line and 1500   Feet From The   East   Line					
15   Township 32N   Ramps 12W   NMPM   San Juan   County   10. Elevrision (Shore whether DF, RAS, RT, GR, etc.)   11.   Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data   NOTICE OF INTENTION TO:   SUBSEQUENT REPORT OF:   REMEDIAL WORK   PLUG AND ABANDON   CHANGE PLANS   COMMENCE DRILLING OPNS.   PLUG AND ABANDONMENT   COMMENCE DRILLING OPNS.   PLUG AND ABANDONMENT   CASING TEST AND CEMENT JOB   OTHER:   O		1710 Feet From The North	Line and 1500	Feet From The East Line	
10.   Elevation (Show whether DF, REB, RT, GR, etc.)   6133 'GL     11.   Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data   NOTICE OF INTENTION TO:   SUBSEQUENT REPORT OF:   PERFORM REMEDIAL WORK	15	201	1.0	_	
NOTICE OF INTENTION TO:    SUBSEQUENT REPORT OF:   PERFORM REMEDIAL WORK		//////////	DF, RKB, RT, GR, etc.)		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OF CASING TEST AND CEMENT JOB OTHER:  12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  05-12-89 Spudded well at 11:30 am 05-12-89. Drilled to 240'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 240'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (182 cu.ft.) circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.  05-14-89 TD 2344'. Ran 54 jts. 7", 20.0#, K-55 intermediate casing, 2332' set @ 2344'. Cemented with 390 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (690 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (122 cu.ft.) circulated to surface. WOC 12 hours. Held 1200#/30 min.  1 hereby perity that the Automation above is give and complete to the boat of my incoming and ballet.  TIME Regulatory Affairs DATE 5-15-89  TYPE OR PRATY HAMB		• • •		=	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER:  12. Describe Proposed or Completed Operations (Clearly state all persinens details, and give persinens dates, including estimated date of starting any proposed work) SEE RULE 1103.  05~12~89 Spudded well at 11:30 am 05~12~89. Drilled to 240'. Ran 5 jts. 9 5/8", 36.0#, K~55 surface casing set at 240'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel~flake and 3% calcium chloride (182 cu.ft.) circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.  05~14~89 TD 2344'. Ran 54 jts. 7", 20.0#, K~55 intermediate casing, 2332' set @ 2344'. Cemented with 390 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (690 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (122 cu.ft.) circulated to surface. WOC 12 hours. Held 1200#/30 min.  1 hereby perfect that the lateronalism bows is the base complete to the bost of my incomplete and belief.  TILE Regulatory Affairs DATE 5~15~89  TRUE TRUETHONE NO.	NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
CASING TEST AND CEMENT JOB  OTHER:  OT	PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		
OTHER:    OTHER:   OTHER:	TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT				
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  05-12-89	PULL OR ALTER CASING CASING TEST AND CEMENT JOB				
Spudded well at 11:30 am 05-12-89. Drilled to 240'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 240'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (182 cu.ft.) circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.  05-14-89  TD 2344'. Ran 54 jts. 7", 20.0#, K-55 intermediate casing, 2332' set @ 2344'. Cemented with 390 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (690 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (122 cu.ft.) circulated to surface. WOC 12 hours. Held 1200#/30 min.  I bendy fartly that the information above is the end complete to the best of my knowledge and belief.  SIGNATURE Regulatory Affairs DATE 5-15-89  TYPE OR FRATT NAME  TELEPHONE NO.	OTHER:				
jts. 9 5/8", 36.0#, K-55 surface casing set at 240'.  Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (182 cu.ft.) circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.  05-14-89  TD 2344'. Ran 54 jts. 7", 20.0#, K-55 intermediate casing, 2332' set @ 2344'. Cemented with 390 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (690 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (122 cu.ft.) circulated to surface. WOC 12 hours. Held 1200#/30 min.  I benety statuty that the lafornation above is the and complete to the best of my knowledge and belief.  SIGNATURE TITLE Regulatory Affairs DATE 5-15-89  TYPE OR FERNT NAME  Original Signed by FRANK T. CHAVEZ					
2332' set @ 2344'. Cemented with 390 sks. Class "B" 65/35  with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (690  cu.ft.) followed by 100 sks. Class "B" with 2% calcium  chloride (122 cu.ft.) circulated to surface. WOC 12 hours.  Held 1200#/30 min.  I hereby settly that the information above is the and complete to the best of my knowledge and bestef.  SKONATURE Regulatory Affairs DATE 5-15-89  TYPE OR PERT NAME  THE REPHONE NO.	jts. 9 5/8", 36.0#, K-55 surface casing set at 240".  Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (182 cu.ft.) circulated to surface. WOC				
TYPE OR FRENT NAME  THE PROOF FOR State Use)  Original Signed by FRANK T. CHAVEZ	2332' set @ 2344'. Cemented with 390 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (690 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (122 cu.ft.) circulated to surface. WOC 12 hours.				
TYPE OR PRINT NAME  (This space for State Use)  Original Signed by FRANK T. CHAVEZ	$\gamma$				
(This space for State Use)  Original Signed by FRANK T. CHAVEZ	SIGNATURE / PAGE	Madfield	Regulator	y Affairs DATE 5-15-89	
Original Signed by FRANK T. CHAVEZ	TYPE OR FRENT NAME			TELEPHONE NO.	
	Original Signed			0,33,31, 0, 10,00	