

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |   |  |  |
|--|---|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |   | REPORT ON REPAIRING WELL                       |  |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |   | REPORT ON PULLING OR OTHERWISE ALTERING CASING |  |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                | X | REPORT ON DEEPENING WELL                       |  |
| REPORT ON RESULT OF PLUGGING OF WELL                       |   |  |  |

Roswell, New Mexico

January 1, 1948

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Richfield Oil Corporation Santa Fe Well No. 2-1 in the \_\_\_\_\_

Company or Operator

Lease

SW  $\frac{1}{4}$  of NE  $\frac{1}{4}$  of Sec. 4, T. 16-N, R. 6-W, N. M. P. M.,

Wildcat Field, McKinley County.

The dates of this work were as follows: December 20, 1947 and December 27, 1947

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on November 29 19 47

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The well was spudded with cable tools on December 19, 1947 and a 15 1/2" hole was drilled to 64'.

Two joints of 10 3/4" --40.5# used casing was cemented at 64' with 30 sacks of El Toro cement. After drilling out, 400# was applied and held for 1/2 hr.

Witnessed by F. L. Campbell Richfield Oil Corp. Engineer  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

day of \_\_\_\_\_ 19 \_\_\_\_\_

Name F. L. Campbell

Position Engineer

Notary Public

Representing Richfield Oil Corporation  
Company or Operator

My commission expires \_\_\_\_\_

Address Hotel Nickson, Roswell, New Mexico

Remarks:

Roy Varbrough

Name

Approved January 6, 1948

Oil & Gas Inspector

Title