

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	/
FILE	/ ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name Hospah Sand Unit
2. Name of Operator Tesoro Petroleum Corporation		8. Farm or Lease Name
3. Address of Operator 8520 Crownhill, San Antonio, Texas 78209		9. Well No. 4
4. Location of Well UNIT LETTER C 330 FEET FROM THE North LINE AND 2970 FEET FROM THE East LINE, SECTION 1 TOWNSHIP 17N RANGE 9W NMPM.		10. Field and Pool, or Wildcat Upper Hospah Sand
15. Elevation (Show whether DF, RT, GR, etc.) 6967' GL		12. County McKinley

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:


SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug and abandon well as follows:

To set 128' plug across Hospah Sand and perforate at approximately 500'.
To set cast iron retainer on wire line at approximately 275' and pump sufficient amount of cement through the retainer to cover the Seven Lakes Sand inside and outside the casing. Will set 10' plug in top and install dry hole marker.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>A. J. Hernandez</u>	TITLE <u>Mgr. of Production Engineering</u>	DATE <u>Sept. 21, 1971</u>
APPROVED BY <u>Emily C. [Signature]</u>	TITLE <u>Asst. Dir. III</u>	DATE <u>9-27-71</u>
CONDITIONS OF APPROVAL, IF ANY:		