Form: 9-881 a (Feb. 1951) c

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Santa Fe. N.M. 3F081171-K 3-1-48 DEC 25 1960

EY CO

		SUBSE	QUENT REPORT OF	WATER SHUT-OFF		
	NOTICE OF INTENTION TO DRILL			SHOOTING OR ACIDIZING		
NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL			QUENT REPORT OF	ALTERING CASING	·	
OTICE OF INTENTION TO ABAN	DON WELL					
(IN	IDICATE ABOVE BY	CHECK MARK NATURE OF	REPORT, NOTICE, OF	OTHER DATA)		
			ee, 10th,) 	, 60	
5 -8 Il No is l	1717 ocated	ft. from_ ${S}$ lin	1485 e and	ft. from $\{E\}$ line of	GESFI/	
See 35	18N	3 *	nupu	(w) / i	sential	
and Sec. No.)	(Tw	pas nd ova I (Range)	(Meri	dian)	JEG 29 19	
(Field)		(County or Subdivision	i)	(State or Territory)	EGON. C	
		1 16608	C+	· · · · · · · · · · · · · · · · · · ·	DIST. 3	
e elevation of the der	rick floor abo	ove sea level Is	rt.		The same of	
		DETAILS OF	WORK			
te names of and expected dep	ths to objective =	ands; show sizes, weights,	and lengths of prop	osed casings; indicate muc	lding jobs, cemen	
ra trettias or with exbectan gab	ing po	ints, and an other import	ant proposed worm			
	77 BAIA	with Rothry .	3-433 A.	top of the Ma		
111 drill 6-1/	E SULU	A b	SETTI 60		Dece	
ill drill 6-1/ le or to a max	leum cem	THE OF INSTRU	(K'4)] m]	401 as 5_	- Fer H	
ill drill 6-1/ le or to a max face casing an	d circul	th or <u>1550</u> .	nt ll pl	age 40' of 8-	5/8"	
ill drill 6-1/ le or to a max face casing an located will r	d circul	ts or 1350°. Ste cement t " caning. ce	nt ll pl	age 40' of 8-	5/8"	
ill drill 6-1/ le or to a max face casing an located will r	d circul	ts or 1350°. Ste cement t " caning. ce	nt ll pl	age 40' of 8-	5/8"	
ill drill 6-1/ le or to a max face casing an located will r	d circul	ts or 1350°. Ste cement t " caning. ce	nt ll pl	age 40' of 8-	5/8"	
ill drill 6-1/ le or to a max face casing an located will r	d circul	ts or 1350°. Ste cement t " caning. ce	nt ll pl	age 40' of 8-	5/8"	
ill drill 6-1/ le or to a max face casing an located will r	d circul	ts or 1350°. Ste cement t " caning. ce	nt ll pl	age 40' of 8-	5/8"	
ill drill 6-1/ le or to a max face casing an located will r	d circul	ts or 1350°. Ste cement t " caning. ce	nt ll pl	age 40' of 8-	5/8"	
ill drill 6-1/ le or to a max face casing an located will r	d circul	ts or 1550. Ste cement t " caning, ce	nt ll pl	age 40' of 8-	5/8"	
ill drill 6-1/ le or to a max face casing an located will r	d circul	ts or 1550. Ste cement t " caning, ce	nt ll pl	age 40' of 8-	5/8"	
ill drill 6-1/ le or to a max face casing an located will r core and run e	d circul: un 4-1/2 lectric	te cement t " caning, ce log on hole.	Will pl O set pro Fest end	ace 40° of 8- perly. If oi perforete. Tx	-5/8# l or ga∎ meet	
ill drill 6-1/le or to a max face casing an located will r core and run e	d circul: In 4-1/2 lectric	te cement t " caning, ce log on hole.	Will pl O set pro Fest end	ace 40° of 8- perly. If oi perforete. Tx	-5/8# l or ga∎ meet	
ill drill 6-1/le or to a max face casing an located will r core and run e	id circul: 2n 4-1/2 lectric f work must recei	to coment to anning, con hole.	Will pl O set pro Fest end	ace 40° of 8- perly. If oi perforete. Tx	-5/8# l or ga∎ meet	
ill drill 6-1/le or to a max face casing an located will record and run end ru	d circulation 4-1/2 lectric	te cement to aning, cellog on hole.	Will pl O set pro Fest end	ace 40° of 8- perly. If oi perforete. Tx	-5/8# l or ga∎ meet	
Ill drill 6-1/le or to a max face casing an located will record and run end ru	id circul: 2n 4-1/2 lectric f work must recei	te cement to aning, cellog on hole.	Will pl の set pro Fett snd	eee 40° of 8- perly. If of 8-	1 or 381	
ill drill 6-1/le or to a max face casing an located will record and run element of the state of	d circulation 4-1/2 lectric	te cement to aning, cellog on hole.	Will pl の set pro Fett snd	ace 40° of 8- perly. If oi perforete. Tx	1 or 381	
ll drill 6-1/ e or to a max ace casing an ceated will r	d circul	ts or 1550. Ste cement t " caning, ce	nt ll pl	age 40' of 8-	5/8"	

13

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

SEE INS	TRUCTIONS FOR COMP		THE REVERSE SIL		
Operator		Lease		Well No.	
Operator J.I.Harvey		Clyde B. F	larvey ST 08	ST 081171-k 5-B	
Unit Letter Section	Township 18 N.	Range 3 W.	County Sand	oval	
Actual Footage Location of Well:	10 4.		<u> </u>		
17/7 feet from the	KINTY line and	1485 feet	from the 30 AS	T. line	
Ground Level Elev. Producing Fo	ormation	Pool		Dedicated Acreage:	
6604 Mesa	lerde	Clyde B.	Harvey	520 160 Acres	
 Is the Operator the only owner in who has the right to drill into and another. (65-3-29 (e) NMSA 193 If the answer to question one is wise? YES NO If the answer to question two is the second of the se	to produce from any pool 35 Comp.) 'no,'' have the interests of answer is "yes,'' Type	of all the owners been co	onsolidated by comm	himself or for himself and	
	no, list all the owners	Land Descript			
Owner Elyde B. Harv	Nenet, Naset, Setset, We see 33, 18n 3W				
			•		
		A STATE OF THE STA			
	SECTION B	JOFF FULL		CERTIFICATION	
	2 70	DEG 29 1960 OIL CON. COM DIST. 3	in SE oplete belief Name Positi	on Character.	
17485			shown plotte survey super and co and be	Surveyed A A C C tered Professional Engineer	
0 330 660 990 1320 1650 1	980 2310 2640 20	00 1500 1000	. Yi'c	Land Surveyor Locate No. L. S. No. 95	

INSTRUCTIONS FOR COMPLETION OF FORM C-128

- 1. Operator shall furnish and certify to the information called for in Section A.
- 2. Operator shall outline the dedicated acreage for both oil and gas wells on the plat in Section B.
- 3. A registered professional engineer or land surveyor registered in the State of New Mexico or approved by the Commission shall show on the plat the location of the well and certify this information in the space provided.
- 4. All distances shown on the plat must be from the outer boundaries of the Section.
- 5. If additional space is needed for listing owners and their respective interests as required in question 3 of Section A, please use space below.

e ţ