For m	9-331
(May	1963)

WELL

## SUBMIT IN TRIPLICATES UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on verse side)

	Form a Budget	pprove Bures	ea. Lu N	0. 42	It	1424
EASE	DESIGN	ATION	AND	SERIA	Ĺ	NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NA

GEOLOGICAL	SURVEY

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS
Do not use this form for Use "Z	or proposals to c APPLICATION	drill er to FOR PER	deepen or plug MIT—" for such	back to proposal	a different reservoir.

				-
7.	UNIT	AGREEMENT	NAME	

SF 078356-A

2.	NAME OF OPERA	TOR	
	El Paso	Natural Gas	Company_

GAS

3. ADDRESS OF OPERATOR

PO Box 990, Farmington, NM 87401 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)

1690' 27 1650' 27 At surface

15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6266 DF 14. PERMIT NO.

S. FARM OR LEASE NAME G. R. Gentle

10. FIELD AND POOL, OR WILDCAT

Fulcher Kutz PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 26, T-27-N, R-9-W

**NMPM** 12. COUNTY OR PARISH 13. STATE New Mexico San Juan

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF FRACTURE TREAT

SHOOT OR ACIDIZE REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT SHOOTING OR ACIDIZING

REPAIRING WELL ALTERING CASING ABANDON MENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* nent to this work.)

Because of its inability to produce gas, it is planned to plug and abandon this well in the following manner:

Run tubing, spot a 50 sk. cement plug over the Pictured Cliffs formation.

Perforate holes at base of the Ojo Alamo and spot a 75 sk. cement plug, displace some cement into the formation, determine the free point of the production casing, shoot off near the free point and spot a 25 sk. cement plug on the casing stub.

Spot a 25 sk. cement plug at the base of the surface casing.

Place a 15 sk. cement plug at the surface. Install a dry hole ariand clean up the location.

6 1973

OIL CON. COM DIST.

18. I hereby certify that the foregoing is true and correct

Drilling Clerk TITLE

August 3, 1973

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: TITLE

3 1973 AUG

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY RECTON, IL