Form 9-3311 (April 1952)	O

1		i	-
	ļ	ļ	
	1	Ì	
l	į		
[1 1	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R359.4. Approval expires 12-31-60.
Indian Agency Navajo
Allottee Tribal

		D REPORTS ON WELLS	
OTICE OF INTENTION TO DRIE		SUBSEQUENT REPORT OF WATER SHUT-OFF	7. C)
OTICE OF INTENTION TO CHAI	NGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
OTICE OF INTENTION TO BED	RILL OR REPAIR WELL	SUBSEQUENT REPORT OF ALTERING CASING	
OTICE OF INTENTION TO SHOO	OT OR ACIDIZE	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO PULL	OR ALTER CASING	SUBSEQUENT REPORT OF ABANDONMENT	XX
NOTICE OF INTENTION TO ABAN	IDON WELL	SUPPLEMENTARY WELL HISTORY	
(INI)	DICATE ABOVE BY CHECK MARK NATU	RE OF REPORT, NOTICE, OR OTHER DATA)	
McMillen #1	******	November 19,	, 1927
ll Nois	located 1682 ft. from	$\left\{\begin{array}{ccc} & & & \\ & & \\ & & \\ & & \\ & & \\ \end{array}\right\}$ line of se	c. 28
8 Sw NE (14 Sec. and Sec. No.)	28N, 16W (Twp.) (Ran	N.M.P.M.	
W. C.		(waturall)	
(Field)	(County or Sub-	New Mexico division) (State or Territory)	
	DETAILS (as to objective sands; show sizes, weights	OF WORK ghts, and lengths of proposed casings; indicate mudding j aportant proposed work)	ohe same
te names of and expected depth	ing points, and all other in	nportant proposed work)	
ll was drilled to -3/4", 32.75#, 8 R was placed from tota. Casing was cation was cleaned	a T.D. of 1524' in the distribution of 1524'	he Dakota. No show of oil or ga cemented through the Tocito. A accomplishing shut-off of water: 2" swage with 2" valve installe filled. The above procedure wa lon to Abandon Well" as approved	s. cement from tl
ll was drilled to -3/4", 32.75#, 8 R Ig was placed from tota. Casing was placed in accordance with a casing was present the secondance with the s	a T.D. of 1524 in the distribution of the	he Dakota. No show of oil or ga cemented through the Tocito. A accomplishing shut-off of water: 2" swage with 2" valve installe filled. The above procedure wa lon to Abandon Well" as approved	s. cement from t
ll was drilled to -3/4", 32.75#, 8 R ag was placed from tota. Casing was cation was cleaned in accordance with a cordance with	a T.D. of 1524 in the distribution of 1524 in the distribution of 1524 in the distribution of 1450 feet and a 10-3/4 x up, cellar and pits the "Notice of Intential and pits and pits and pits the "Notice of Intential and pits and	he Dakota. No show of oil or ga cemented through the Tocito. A accomplishing shut-off of water: 2" swage with 2" valve installe	s. cement from t
ll was drilled to -3/4", 32.75#, 8 R ag was placed from cota. Casing was cation was cleaned in accordance with a cordance with	a T.D. of 1524 in the distribution of 1524 in the distribution of 1524 in the distribution of 1450 feet and a 10-3/4 x up, cellar and pits the "Notice of Intential and pits and pits and pits the "Notice of Intential and pits and	he Dakota. No show of oil or ga cemented through the Tocito. A accomplishing shut-off of water: 2" swage with 2" valve installe filled. The above procedure wa lon to Abandon Well" as approved	s. cement from t d.