REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF 047019 A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas 🖂	Summit
well well other	9. WELL NO.
2. NAME OF OPERATOR	29 4
Union Texas Petroleum Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Fulcher Kutz Pictured Cliffs
P.O. Box 1290, Farmington, New Mexico 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Section 33, T29N-R11W NMPM
AT SURFACE: 990' FNL; 990' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	San Juan New Mexico
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)

5541 GL

(NOTE: Report results of multiple completion or z PULL OR ALTER CASING change on Form 9-330.) MULTIPLE COMPLETE **CHANGE ZONES** ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SUBSEQUENT REPORT OF:

- 1. MIRUSU. Pull 1-1/4" tubing.
- 2. Clean out to TD.
- 3. Refrac P.C. perfs w/50,000# sand.
- 4. Clean out to TD and return to production.

		Set @ Ft.
18. I hereby certify that the foregoing is to SIGNED W. K. COOPER	rue and correct Manager-District 	November 15, 1983
(This space for Federal or State office use)		
APPROVED BY		ACCEPTED FOR RECORD

NOV 1 8 1983

*See Instructions on Reverse Side

PARMINUTUR RESUDENCE AREA 5mm