NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

tional instructions in the Rules and Regul	Indicate Nature of Notice	e by Checking Belov	▼	
Notice of Intention to Change Plans	Notice of Intention to Temporarily Abandon W	VELL	Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well	Notice of Intention to Plug Back		Notice of Intention to Set Liner	
Notice of Intention to Squeeze	Notice of Intention to Acidize		Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	Notice of Intention (Other)		Notice of Intention (Other)	
OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO	Aztec, New M		otember 18, 1953	
Gentlemen: Following is a Notice of Intention to	do cartain work as described b	nelow at the		
_			Masden-Selby	
Company or Opera	.tor)		Well No3in.	(Tinit)
NE 1/4 NE 1/4 of Sec. 28 (40-acre Subdivision)	l, T 29N , R]	11%,NMPM., .	Fulcher-Kutz	Peo
San Juan			•	
(FOLLO Spot 30-sack cement plug	JLL DETAILS OF PROPONE INSTRUCTIONS IN THE	E RULES AND RE	GULATIONS)	ling at
	in Farmington sandst	tone, starting	gulations) g at T.D. and extend face casing, and le	ave
Spot 30-sack cement plug least 100 feet into the 5	in Farmington sandst	tone, starting	gulations) g at T.D. and extend face casing, and le	ave
Spot 30-sack cement plug least 100 feet into the 5	in Farmington sandst	tone, starting	gulations) g at T.D. and extend face casing, and le	ave
Spot 30-sack cement plug least 100 feet into the 5	in Farmington sandst	tone, starting	gulations) g at T.D. and extend face casing, and le	ave
Spot 30-sack cement plug least 100 feet into the 5 with a marker at least 4"	in Farmington sandst	tone, starting ck plug in suring at least 4	gulations) g at T.D. and extend face casing, and le	level.
Spot 30-sack cement plug least 100 feet into the 5	in Farmington sandsti-1/2" casing; 10-sad in diameter extendi	tone, starting ck plug in suring at least 4	egulations) g at T.D. and exterior face casing, and le feet above ground Company or Operator	level.
Spot 30-sack cement plug least 100 feet into the 5 with a marker at least 4" Approved	in Farmington sandsti-1/2" casing; 10-sad in diameter extendi	tone, starting the plug in suring at least 4	at T.D. and extend face casing, and le feet above ground V.T. Drilling Components Company or Operator	level.
Spot 30-sack cement plug least 100 feet into the 5 with a marker at least 4 description of the sack and seed as follows:	in Farmington sandsti-1/2" casing; 10-sad in diameter extendi	tone, starting ck plug in sur ing at least 4 Haynes &	at T.D. and extend face casing, and le feet above ground V.T. Drilling Components Company or Operator	level.

AZTEC DIS	
No. Copies Rece	ived 💪
DISTE	RIBUTION
an gagain ta ki shaqada adan qaran shakaran in shaqan da saarka — saa ka saar ka saa saa saa saa saa saa saa s	NO.
Operator	1
Santa Fe	
Proration Office	
State Land Office	
U. S. G. S.	
Transporter	
File	