

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name Gallegos Canyon Unit
2. Name of Operator AMOCO PRODUCTION COMPANY (Formerly Stanolind Oil & Gas Company)		8. Farm or Lease Name Gallegos Canyon Unit
3. Address of Operator 501 Airport Drive, Farmington, New Mexico 87401		9. Well No. 27
4. Location of Well UNIT LETTER K 1650 FEET FROM THE South LINE AND 1650 FEET FROM THE West LINE, SECTION 30 TOWNSHIP 29-N RANGE 12-W NMPM.		10. Field and Pool, or Wildcat West Kutz-Pictured Cliffs
15. Elevation (Show whether DF, RT, GR, etc.) NA		12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>


SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 11-29-55 moved in cable tool rig. Rigged up 11-30-55 and started cleaning out. Cleaned out to TD 1300' 12-3-55, spotted 25 sack cement plug over Pictured Cliffs. Spotted 9.6# mud to 120'. Spotted 25 sack cement plug from 120' to surface. Plug did not cover Farmington sand. 12-5-55 cleaned out to 550' and spotted 50 sack cement plug to shut off Farmington sand 550' to 420'. Plug did not cover Farmington sand. 12-6-55 drilled to hard cement at 490'. Pumped 15# cement from 490' to surface. Erected abandonment marker and restored ground level to original contour.

NOTE: Delayed report to complete record taken from well file data and daily drilling reports.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED L.O. Jones

TITLE Area Superintendent

DATE April 12, 1971

APPROVED BY Emery Chandel

TITLE Supervisor

DATE APR 13 1971

CONDITIONS OF APPROVAL, IF ANY: