

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

96 AUG 15 PM 3:01

1. Type of Well
GAS

RECEIVED
AUG 21 1996

070 FARMINGTON, NM

2. Name of Operator
MERIDIAN OIL

OIL CON. DIV.
DIST. 3

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
2310' FSL, 2310' FEL, Sec. 19, T-29-N, R-11-W, NMPM

J

5. Lease Number
SF-077056
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Cozzens #5
9. API Well No.
30-045-08017
10. Field and Pool
Fulcher Kutz Pict. Cliff
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

7-31-96 MIRU. SDON.

8-1-96 ND WH. NU BOP. TOOH w/82 jts 1" tbgs. TIH W/3 1/2" gauge ring to 1700'. TOOH. TIH w/BP, set @ 1650'. TOOH. TIH to 1650'. Circ hole clean w/9 bbl wtr. PT csg to 500 psi/5 min, OK. Plug #1: pump 13 sx Class "B" cmt @ 1351-1650'. TOOH. TIH, perf 4 sqz holes @ 1325'. TOOH. (Verbal approval to change plans from J. Morris, BLM). Establish injection. Plug #2: pump 79 sx Class "B" cmt outside csg @ 1225-1325', pump 10 sx Class "B" cmt inside csg, TOC @ 1095'. WOC. SDON.

8-2-96 TIH, tag TOC @ 1113'. TOOH to 592'. Perf 4 sqz holes @ 592'. TOOH. Establish injection. Plug #3: pump 135 sx Class "B" cmt outside csg @ 492-592', pump 7 sx Class "B" cmt inside csg. TOOH. WOC. TIH, tag TOC @ 340'. TOOH to 320'. Perf 4 sqz holes @ 320'. TOOH. Establish injection. Plug #4: pump 135 sx Class "B" cmt outside csg @ 220-320', pump 7 sx Class "B" cmt inside csg. WOC. TIH, tag TOC @ 146'. TOOH to 90'. Perf 2 sqz holes @ 90'. TOOH. Establish circ dow csg & out bradenhead w/27 bbl wtr. Plug #5: pump 79 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 8-2-96.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 8/12/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any: _____

FILED

AUG 16 1996

Gene Spencer

11000