

(SUBMIT IN TRIPLICATE)


UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 065557
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)



November 6, 1953


Well No. 5 is located 880 ft. from N line and 440 ft. from E line of sec. 1313 Sec. 13 (Sec. No.) 29N (Twp.) 13E (R.) N.M.P.M. (Meridian)Fulcher (Name) San Juan (County or Subdivision) New Mexico (State or Territory)The elevation of the derrick floor above sea level is 5,675 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

October 16, 1953 - Open flow test by pitot tube - 689 mcf per day, moved on cable tools for purpose of cleaning out and shooting with S.H. Cleaned out to 1871, ran Schlumberger Gamma Ray-Neutron log. Bottom of 7" casing - 1780'. Shot with 165 qts S.H. on October 22nd. Drilled calseal and gravel plug, unloaded hole and cleaned out to bottom. Landed 1" tubing @ 1865'. Open flow test by pitot tube after workover - 2,995 mcf per day.

Shot Record: T.D. 1850'
T.S. 1797'
T.G. 1793'
T. Calseal plug 1745'



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Carroll & CornellAddress P.O. Box 337, Farmington, N.M.By R. OwenTitle Lease Foreman