

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

660' FSL, 1980' FWL, Sec. 12, T-29-N, R-12-W, NMPM

5. Lease Number  
SF-076465

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name & Number  
Cornell SRC #3

9. API Well No.  
30-045-08435

10. Field and Pool  
Fulcher Kutz Pict. Cliffs

11. County and State  
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

12-31-96 MIRU. TIH, 1" tbg parted. ND WH. NU BOP. SD for holiday.  
1-2-97 TIH, tag fish @ 20'. TOOH w/88 jts 1" tbg. TIH w/gauge ring to 1815'. TOOH.  
TIH w/3 1/2" CIBP, set @ 1807'. TOOH. TIH, tag CIBP @ 1807'. TOOH to 1798'.  
Load hole w/14 bbl wtr. PT csg to 500 psi/15 min, OK. Plug #1: pump 17 sx  
Class "B" neat cmt @ 1404-1798'. TOOH. TIH, perf 3 sqz holes @ 681'. TOOH.  
Establish injection. Plug #2: pump 247 sx Class "B" neat cmt @ 377-681'.  
SDON.  
1-3-97 TIH, tag plug #2 @ 407'. TOOH. TIH, perf 3 sqz holes @ 70'. TOOH. Establish  
circ down csg & out bradenhead. Plug #3: pump 51 sx Class "B" neat cmt down  
csg 3 1/2" csg from 407' to surface. Circ 0.5 bbl cmt to surface. WOC. ND BOP.  
Cut off WH. Install dry hole marker w/20 sx Class "B" neat cmt. RD. Rig  
released. Well plugged and abandoned 1-3-97.

14. I hereby certify that the foregoing is true and correct.

Signed AS/ Duane W. Spencer Title Regulatory Administrator Date 2/6/97

(This space for Federal or State Office use)

APPROVED BY AS/ Duane W. Spencer Title

CONDITION OF APPROVAL, if any:

RECEIVED  
FEB 14 1997

FEB 12 1997

OIL CON. DIV.  
BUREAU