

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 06555 7

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Producing Royalties Inc		8. FARM OR LEASE NAME Carol Cornell	
3. ADDRESS OF OPERATOR Box 1071 Lubbock, Texas 79408		9. WELL NO. 10	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface H 990 FNL # 990 FEL Sec. 11 T29N, R12W, SAN JUAN Co. N.M.		10. FIELD AND POOL, OR WILDCAT M.V.	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 11, T29N R12W NMPM	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5789		12. COUNTY OR PARISH SAN JUAN	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well has been Plugged & ABANDONED as follows:

4-6-76 Moved in equipment. Pick up 2 5/8" tbg
RAN tbg to TD. Spot 80% cement Plug
from 4495' to 4060'. Pulled tbg.

4-7-76 Set casing jacks. Work casing.

4-8-76 Shot 7" casing off @ 1998'
Pull casing.

4-9-76 RAN tbg to 2100', Spot 80% plug
from 2100 to 1800'; Pull tbg to 750'

4-10-76 Spot 50% plug from 50 to 600'
INSTALL P&A MARKER w/ 105X Surface Plug.
Clean loc.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

JUN 29 1978

P. T. McGRATH

DISTRICT ENGINEER

*See Instructions on Reverse Side