

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. SANTA FE 079511
2. NAME OF OPERATOR Blackwood & Nichols Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 1237, Durango, Colorado 81301		7. UNIT AGREEMENT NAME Northeast Blanco Unit No. 1, Sec. 929
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 350' F/SL - 1890' F/WL		8. FARM OR LEASE NAME Northeast Blanco Unit
14. PERMIT NO.		9. WELL NO. 635R
15. ELEVATIONS (Show whether or not XX is in c.) 6073' GR		10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SW/4 Sec. 13-30N-8W
		12. COUNTY OR PARISH San Juan
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL


ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 7-16-75, perforated the Point Lookout Zone, one hole per foot; 5185' - 5210', 5222' - 5228', 5238' - 5244', 5260' - 5290', 5302' - 5312', 5388' - 5392', 5416' - 5424', 5440' - 5448', 5470' - 5476', 5490' - 5496', 5522' - 5528'.

Sand-water fractured with 42,000 Gals. water and 30,000 lbs. 20-40 sand, 150 lbs. FR-20; twenty-five 7/8", RCN balls, average injection rate 59 bbls./min. Average pressure, 1750 PSI.



18. I hereby certify that the foregoing is true and correct

SIGNED DeLasso Loos

TITLE District Manager

DATE 7-22-75

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE