## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

5. 11 ASI

SF=079691 . 6. If indian, allottle or terrename

	-3
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a difference reservoir. Use Form 9–331–C for such proposals.)	
reservoir, use rorm 9-331-C for such proposals.	8. FARM OR LEASE NAME
1. oil gas well other	MUDGE
	9. WELL NO.
2. NAME OF CPERATOR	6A
EL PASO NATURAL GAS CO.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	BLANCO MESA VERDE
BOX 990, FARMINGTON, NEW MEXICO	11. SEC., T., R., M., OR B! K. AND SURVEY OR AREA CO. 11. TO 71. N. D. 11. M
<ol> <li>LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 1 below.)</li> </ol>	occ. 11, 1-51-W, K-11-W
AT SURFACE: 970'N, 1750'W	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	1
AT TOTAL DEPTH:	SAN-JUAN NEW MEXICO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW OF, POL. ARE WELL
	5916' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT BEPORT OF:	the same and the same of the s
TEST WATER SHUT-OFF X	
FRACTURE TREAT SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING []	change on Form 9–330.)
MULTIPLE COMPLETE	·
CHANGE ZONES	
ABANDON* [] [] [] [] (other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly's including estimated date of starting any proposed work, if well is measured and true vertical depths for all markers and zones portain the starting and true vertical depths for all markers and zones portain the starting and true vertical depths for all markers and zones portain the starting and true vertical depths for all markers and zones portain the starting and true vertical depths for all markers and zones portain the starting and true vertical depths for all markers and zones portain the starting and proposed work.	is directionally drilled, give subsurface locations and nent to this work.)*
	40 surface casing, 224' set at 237'
	nt. Circulated to surface. WOC
12 hours; held 600%/30 minutes	
,	
Subsurface Safety Valve: Manu. and Type	Set @
18. Thereby certify that the foregoing is true and correct	
SIGNED: Chieffyeth State Torce Drilling	Clerk DATE 11/21/77
(This space for Federal or State	: office use)
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	

RECEIVED

NOV 281977